

**Product Change Notice**

**Issue Date: 28 April 2015**

**Change Type:**

Datasheet Specification Change. There is no change in material or process.

**Parts Affected:**

ACPL-302J-000E	ACPL-302J-500E
----------------	----------------

All associated options and specials will also be affected.

**Description and Extent of Change:**

1. Tighten Regulated  $V_{CC2}$  Voltage Limits

Regulated $V_{CC2}$ Voltage	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Current Specification	$V_{CC2}$	18	20	22	V	$I_{COMP} = 0A$
New Specification	$V_{CC2}$	19	20	21.5	V	

2. Change in Recommended Operating Conditions

Negative Output IC Supply Voltage	Symbol	Min.	Max.	Units
Current Recommendation	$V_{EE2} - V_E$	-10	0	V
New Recommendation	$V_{EE2} - V_E$	-8	0	V

3. Change in Absolute Maximum Ratings

Negative Output Supply Voltage	Symbol	Min.	Max.	Units
Current Absolution Maximum Rating	$V_{EE2} - V_E$	-15	0.5	V
New Absolution Maximum Rating	$V_{EE2} - V_E$	-10	0.5	V

**Reasons for Change:**

Customers request tightened application conditions to be reflected in datasheet.

**Effect of Change on Fit, Form, Function, Quality, or Reliability:**

All other remaining electrical specifications in datasheet and fit, form, function have not been changed.

**Effective Date of Change:**

Implementation of tightened specification limits will be effective from product date code **1518** (yyww) inclusive, product marking **1518** (yyww).

These changes have been reviewed and approved by Avago Technologies engineers and managers per Avago Technologies procedure: Change Control and Customer Notification, A-5962-6052-80.

Please contact your Avago Technologies field sales engineer or Contact Center (<http://www.avagotech.com/contact/>) for any questions or support requirements. Please return any response as soon as possible, but not to exceed 30 days.