

12500 TI Boulevard, MS 8640, Dallas, Texas 75243

PCN# 20160615001 Qualification of RFAB for Select LBC8 Devices Change Notification / Sample Request

Date: 6/21/2016

To: Newark/Farnell PCN

Dear Customer:

This is an announcement of a change to a device that is currently offered by Texas Instruments. The details of this change are on the following pages.

We request you acknowledge receipt of this notification within **30** days of the date of this notice. Lack of acknowledgement of this notice within 30 days constitutes acceptance of the change. If you require samples or additional data to support your evaluation, please request within 30 days.

The proposed first ship date is indicated on page 3 of this notification, unless customer agreement has been reached on an earlier implementation of the change.

This notice does not change the end-of-life status of any product. Should product affected be on a previously issued product withdrawal/discontinuance notice, this notification does not extend the life of that product or change the life time buy offering/discontinuance plan.

For questions regarding this notice, contact your local Field Sales Representative or the PCN Manager (PCN www admin team@list.ti.com).

Sincerely,

PCN Team SC Business Services

20160615001 Attachment: 1

Products Affected:

The devices listed on this page are a subset of the complete list of affected devices. According to our records, these are the devices that you have purchased within the past twenty-four (24) months. The corresponding customer part number is also listed, if available.

DEVICE DRV8711DCP

CUSTOMER PART NUMBER

null

Technical details of this Product Change follow on the next page(s).

PCN Number:			20160615001					PCN Date:		ite:	06/21/2016	
Title: Qualification				FAE	B fo	r Select LBC	8 Devices					
Customer Contact:				PCN Manager De			Dept	:	: Quality Services		ity Services	
Proposed 1 st Ship Date			:	09/21/2016 Estimated Sample Availability:			ple		Date provided at sample request.		•	
Change Type:												
Assembly Site					Assembly Process			Assembly Materials				
Design		1				Electrical Specification			Mechanical Specification			
Test Site		ite				Packing/Shipping/Labeling				Test Process		
						Wafer Bump Material				Wafer Bump Process		
						Wafer Fab Materials			Wafer Fab Process			
Part number change												
PCN Details												

Description of Change:

Texas Instruments is pleased to announce the qualification of its RFAB fabrication facility as an additional wafer Fab source for the selected devices listed in "Product Affected" section.

	Curre	nt Sites		Additional Sites			
Current Fab Site	Fab Process	Bump Site	Wafer Diameter	Additional Fab Site	Fab Process	Bump Site	Wafer Diameter
DP1DM5	LBC8	DBUMP	200 mm	RFAB	LBC8	Clark-BP	300 mm

Qual details are provided in the Qual Data Section.

Reason for Change:

Continuity of Supply

Anticipated impact on Form, Fit, Function, Quality or Reliability (positive / negative):

None

Changes to product identification resulting from this PCN:

Current

Chip Sites	(20L)	Chip Site Country Code (21L)	Chip Site City	
DP1DM5	DM5	USA	Dallas	
New				
Chip Site	Chip Site Origin Code (20L)	Chip Site Country Code (21L)	Chip Site City	

Sample product shipping label (not actual product label)



RFAB



RFB

(1P) \$N74L\$07N\$R (Q) 2000 (D) 0336 (31T) LOT: 3959047MLA (4W) TKY(1T) 7523483\$12 (P) (2P) REV: (V) 0033317 (20L) CSO: SHE (21L) CCO: USA (22L) ASO: MLA (23L) ACO: MYS

USA

Richardson

Product Affected:		
DRV8711DCP	DRV8711DCPR	

Qualification Report

LBC8 Offload from DM5 to RFAB; Gort (DRV8711DCP) Approve Date 03-Jun-2016

Product Attributes

Attributes	Qual Device: DRV8711DCP (GORT)	QBS Product Reference: DRV8711DCP	QBS Process Reference: SN96019PFP	QBS Package Reference: ALM2402QPWPRQ1	QBS Package Reference: TAS5548DCA
Assembly Site	TI TAIWAN	TAI / TITL	PHI (TIPI)	TAI (TITL)	TAI
Package Family	HTSSOP	HTSSOP	HTQFP	HTSSOP	HTSSOP
Wafer Fab Supplier	RFAB	DM0S5	RFAB	RFAB/DMOS6	RFAB
Wafer Fab Process	LBC8	LBC8	LBC8	LBC7	1833C05

⁻ QBS: Qual by Similarity

Qualification Results Data Displayed as: Number of lots / Total sample size / Total failed

Туре	Test Name / Condition	Duration	Qual Device: DRV8711DCP (GORT)	QBS Product Reference: DRV8711DCP	QBS Process Reference: SN96019PFP	QBS Package Reference: ALM2402QPWPRQ1	QBS Package Reference: TAS5548DCA
AC	Autoclave 121C	96 Hours	-	-	3/240/0	3/255/0	3/240/0
CDM	ESD CDM	+/- 1000V	1/3/0	-	-	-	-
ED	Auto Electrical Distributions	Cpk>1.67 Room, hot, and cold test	-	-	-	3/90/0	-
ED	Electrical Characterization	Per Datasheet Parameters	1/Pass	-	-	-	-
HAST	Biased HAST, 130C/85%RH	96 hours	-	-	3/240/0	3/253/0	-
HBM	ESD - HBM	2500 V	1/3/0	-	-	-	1/3/0
HTOL	Life Test, 125C	1000	-	-	3/239/0	-	-
HTSL	High Temp Storage Bake 170C	420 Hours	-	-	3/240/0	-	3/240/0
LU	Latch-up	(per JESD78)	1/6/0	-	1/6/0	-	1/6/0
MQ	Manufacturability (Assembly)	(per mfg. Site specification)	-	-	1/Pass	-	3/Pass
MQ	Manufacturability (Wafer Fab)	(per mfg. Site specification)	1/Pass	1/Pass	1/Pass	-	-
тс	Temperature Cycle, - 65/150C	500 Cycles	-	-	3/231/0	3/260/0	3/240/0

⁻ Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable

Quality and Environmental data is available at TI's external Web site: http://www.ti.com/

Green/Pb-free Status:

Qualified Pb-Free (SMT) and Green

For questions regarding this notice, e-mails can be sent to the regional contacts shown below, or you can contact your local Field Sales Representative.

Location	E-Mail
USA	PCNAmericasContact@list.ti.com
Europe	PCNEuropeContact@list.ti.com
Asia Pacific	PCNAsiaContact@list.ti.com
Japan	PCNJapanContact@list.ti.com

⁻ Qual Device DRV8711DCP (GORT) is qualified at LEVEL2-260C

⁻ The following are equivalent HTOL options based on an activation energy of 0.7eV: 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours

⁻ The following are equivalent HTSL options based on an activation energy of 0.7eV: 150C/1k Hours, and 170C/420 Hours

⁻ The following are equivalent Temp Cycle options per JESD47: -55C/125C/700 Cycles and -65C/150C/500 Cycles