

COOLSPICE CONNECTORS

LARGE WIRE

TE Connectivity's (TE) CoolSplice Connector portfolio has been expanded to include connectors suitable for larger wire sizes. All CoolSplice connectors allow for push button termination using a common pair of pliers. Both wires are terminated independently for ease of use, and this feature allows for factory pre-termination of one wire and field termination of the second during installation. All CoolSplice connectors offer a gel-filled sealed version of the standard product extending use of CoolSplice into harsh environment applications requiring ingress protection from the elements. A thoughtful design includes a clear body material for visual inspection of the termination and to distinguish between our standard and sealed product. Red, yellow & blue color coded termination buttons take the guess work out of matching wire size to appropriate connector.



Applications

- **Outdoor Lighting**
 - Roadway Street and Area
 - Signs and Building Façade
 - Architectural
 - Bridge and Tunnel
- **Indoor Lighting Fixtures**
- **Wiring Harness Field Repairs**

Electrical

- **Current / Voltage Rating:**
 - 14 AWG wire - 15A Max at 600V AC/400V DC
 - 16 AWG wire - 15A Max at 600V AC/400V DC
 - 18 AWG wire - 10A Max at 600V AC/400V DC
- **Dielectric Withstanding Voltage:**
 - 3400 VAC

Mechanical

- Ambient temperature between -40 C and 75 C
- CoolSplice operating temperature between -40 C and 105 C
- IP20, IPX5, IPX7 and IPX8 rating (2 hours, 1m under water)

Specifications

- Product Specification: [108-133061](#)
- Application Specification: [114-133061](#)

Key Benefits

- Enable a waterproof solution with an IP rated splice
- Easy factory or field installation using independent push button termination for left and right side of the connector
- Save installation time and eliminate the need to pre-strip wires with insulation displacement technology (IDC)
- Inventory three P/Ns to accommodate eight different wire combinations







Product Compliance / Approvals

- IEC 60998-2-3
- UL 486C

Materials


- Tin plated, copper alloy insulation displacement contacts
- UL 94V-2

Product Selection Information

	Description	Wire Size*	Sealed (Y/N)	Part Number
	CoolSplice Connector Large Wire	12/14 - 14/16 AWG 4.0/2.5 - 2.5/1.5 mm ²	Y	2213600-1
	CoolSplice Connector Large Wire	12/14 - 16/18 AWG 4.0/2.5 - 1.0/0.75 mm ²	Y	2213600-2
	CoolSplice Connector Large Wire	14/16 - 16/18 AWG 2.5/1.5 - 1.0/0.75 mm ²	Y	2213600-3
	CoolSplice Connector Large Wire	12/14 - 14/16 AWG 4.0/2.5 - 2.5/1.5 mm ²	N	2213600-4
	CoolSplice Connector Large Wire	12/14 - 16/18 AWG 4.0/2.5 - 1.0/0.75 mm ²	N	2213600-5
	CoolSplice Connector Large Wire	14/16 - 16/18 AWG 2.5/1.5 - 1.0/0.75 mm ²	N	2213600-6

*Wire sizes corresponding to IEC60998-1

Dimensions



te.com

© 2016 TE Connectivity Ltd. Family of Companies. All Rights Reserved. CoolSplice, TE, TE Connectivity, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and Company names mentioned herein may be trademarks of their respective owners.
1-1773884-7 JN 10/2016

USA: +1 (800) 522-6752
Canada: +1 (905) 475-6222
Mexico: +52 (0) 55-1106-0800
Latin/S. America: +54 (0) 11-4733-2200
Germany: +49 (0) 6251-133-1999

UK: +44 (0) 800-267666
France: +33 (0) 1-3420-8686
The Netherlands: +31 (0) 73-6246-999
China: +86 (0) 400-820-6015