

Waterproof Voltage Tester



General Characteristics

Power	: 1.5V Batteries (R03) × 2
LCD Size	: 23mm × 12mm
Product Colour	: Orange and Grey
Product Net Weight	: 210g
Product Size	: 275mm × 51mm × 30mm
Standard Accessories	: Batteries

Specifications:

Basic Functions	Range	Best Accuracy
LED AC/DC Voltage Indication (V)	12V	0 to 12V
	24V	19V ±2V
	50V	48V ±6V
	120V	110V ±20V
	230V	200V ±20V
	400V	340V ±30V
	690V	520V ±30V
Phase Rotation Test	Operating Voltage: 0V to 690V Frequency: 50Hz to 60Hz	√
Single Lead(L2)Voltage Detection	Operating Voltage: 0V to 690V Frequency: 50Hz to 400Hz	√
Continuity Test	Resistance: 0 to 100kΩ Beeper and LED light Indicator	√
Polarity Detection	Positive & Negative	√
Water-Proof (IP65)		√
Auto Range		√
Work Light		√
Low Battery Indication	Short circuit two leads, LED and beeper off when the battery is low	√
LCD AC/DC Voltage Display	24V to 690V	±(3%+5)

Part Number Table

Description	Part Number
Waterproof Voltage Tester	72-3565

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell plc 2012.

