

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Name of product	Fast-Metal Minute Adhesive Resin Code-Nr. 105511
1.2. Relevant identified uses of the substan Recommended intended purpose(s) 2-Component Epoxy Resin - Resin Componen	Ŭ
1.3. Details of the supplier of the safety data	a sheet
Distributor	WEICON GmbH & Co. KG Königsberger Str. 255,, DE-48157 Münster Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244 E-Mail : msds@weicon.de Internet : www.weicon.de
Advice	Produktsicherheit / Product-Safety-Department Phone ++49(0)251 / 9322 - 0 E-mail (competent person): msds@weicon.de
1.4. Emergency telephone number	
	EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English) TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)
Manufacturer	WEICON GmbH & Co. KG Königsberger Str. 255, DE-48157 Münster
1.4. Emergency telephone number	
,,	GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h): Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and categories	d Hazard Hazard Statements Classification procedure		
Skin Irrit. 2	H315		
Eye Irrit. 2	H319		
Skin Sens. 1	H317		
Aquatic Chronic 2	H411		
Hazard Statement	S		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H319	Causes serious eye irritation.		
H411	Toxic to aquatic life with long lasting effects.		



workplace.

2.2. Label elements Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS09

Signal word Warning

D102

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the
P273	Avoid release to the environment.

- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P305 + P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P338
- P332 + P313 If skin irritation occurs: Get medical advice/attention.
- If skin irritation or rash occurs: Get medical advice/attention. P333 + P313
- P337 + P313 If eye irritation persists: Get medical advice/attention.
- Take off contaminated clothing. P362
- Wash contaminated clothing before reuse. P363
- P391 Collect spillage.
- P501 Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Special rules for supplemental label elements for certain mixtures Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients

3.1. Substances not applicable

3.2. Mixtures

Description

Resin for a two-component epoxy adhesive



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH) Printed 02.09.2016 revision 03.08.2016 (GB) Version 8.3

Fast-Metal Minute Adhesive Resin

Hazardous	ingredients			
CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
100-51-6	202-859-9	benzyl-alcohol	1 - 5	Acute Tox. 4, H332 / Acute Tox. 4, H302
25068-38-6	500-033-5	reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	30 - 50	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
2425-79-8	219-371-7	1,4-bis(2,3-epoxypropoxy)butane	1 - 5	Acute Tox. 4, H332 / Acute Tox. 4, H312 / Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317
28064-14-4	polymer	Reaction Product of Phenol- Formaldehyde Novolac and Epichlorohydrin	1 - 5	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
REACH				
CAS No	Name			REACH registration number
100-51-6	benzyl-alcoh	ol		01-2119492630-38-xxxx
25068-38-6	•	luct: bisphenol-A-(epichlorhydrin) epoxy resin (numbe eight <= 700)	er average	01-2119456619-26-xxxx
2425-79-8	1,4-bis(2,3-e	poxypropoxy)butane		01-2119494060-45-xxxx

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately and dispose it safely.

In case of inhalation

Ensure of fresh air. In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water. Consult a doctor if skin irritation persists.

In case of eye contact

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

In case of ingestion

Do not induce vomiting. Call for a doctor immediately. Rinse out mouth and give plenty of water to drink.

4.2. Most important symptoms and effects, both acute and delayed

Physician's information / possible symptoms Coughing vomiting Headache Allergic symptoms Nausea skin irritation

Physician's information / possible dangers Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed No information available.



SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Alcohol-resistant foam Dry fire-extinguishing substance Carbon dioxide Water spray jet

Unsuitable extinguishing media Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible. Carbon monoxide (CO) Carbon dioxide (CO2)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Ensure adequate ventilation. Use personal protective clothing. Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, sawdust, general-purpose binder). After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of aerosols. Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace. Open and handle container with care!

General protective measures

Avoid contact with eyes and skin Do not inhale gases/vapours/aerosols.



Hygiene measures

At work do not eat, drink and smoke. Remove soiled or soaked clothing immediately. Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities Requirements for storage rooms and vessels

Keep in closed original container.

Advice on storage compatibility

Do not store with acids or alkalies. Do not store together with animal feedstuffs. Do not store together with food. Do not store together with oxidizing agents.

Further information on storage conditions

Protect from direct solar radiation. Store container at cool and aired place. Storage temperature between 10°C to 30°C (=50°F to 86°F). Protect from heat/overheating.

7.3. Specific end use(s) Recommendation(s) for intended use See section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters DNEL-/PNEC-values DNEL worker

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	12,25 mg/m3	DNEL long-term inhalative (systemic)	
		8,33 mg/kg bw/day	DNEL long-term dermal (local)	
		8,33 mg/kg bw/day	DNEL long-term dermal (systemic)	
PNEC				
CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-	0,006 mg/l	PNEC aquatic, freshwater	
	(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	, e e e e		
	(epichlorhydrin) epoxy resin (number	0,0006 mg/l	PNEC aquatic, marine water	
	(epichlorhydrin) epoxy resin (number			
	(epichlorhydrin) epoxy resin (number	0,0006 mg/l 10 mg/l	PNEC aquatic, marine water	

Additional advice

The statutory local and national regulations have to be observed.



8.2. Exposure controls

Respiratory protection

Breathing apparatus in the event of aerosol or mist formation.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: natural rubber, 0,6mm; 480min; 60min;

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties

9.1. Information on b	pasic physical and chemical properties	
Appearance	Colour	Odour
pasty	black	characteristic
Odour threshold not determined		

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	> 100 °C				
Melting point / Freezing point	not determined				
Flash point	no				
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	not determined				
Self ignition temperature	not determined				
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined				



Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Printed 02.09.2016 revision 03.08.2016 (GB) Version 8.3 Fast-Metal Minute Adhesive Resin

	Value	Temperature	at	Method	Remark
Relative density	ca. 1,9				
Vapour density	not determined				
Solubility in water					soluble
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity	not determined				
Oxidising properties No information available.					
Explosive properties No information available.					
9.2. Other information No information available.					

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidising agents. Reactions with oxidising agents. If heating up polymerisation. Reactions with amines.

10.4. Conditions to avoid

Keep away from heat. If heating up polymerisation.

10.5. Incompatible materials

Substances to avoid Alkali (lye) Amines Acid, concentrated Oxidising agent

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide. Toxic gases/vapours



Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

Skin irritation irritant Eye irritation irritant Skin sensitization sensitizing Experiences made from practice sensitization through skin contact possible. Risk of strong eye injuries. Irritates eves and skin.		Value/Validation	Species	Method	Remark	
Skin sensitization sensitizing Experiences made from practice Sensitization through skin contact possible. Risk of strong eye injuries.	Skin irritation	irritant				
Experiences made from practice Sensitization through skin contact possible. Risk of strong eye injuries.	Eye irritation	irritant				
Sensitization through skin contact possible. Risk of strong eye injuries.	Skin sensitization	sensitizing				
	Sensitization through s	skin contact possible. ries.				

The product is to be handled with the caution usual with chemicals. Other hazardous properties may not be excluded.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

E	Elimination rate	Method of analysis	Method	Validation	
Biological degradability				not degradable	
12.3. Bioaccumulative p No information available.	otential				
12.4. Mobility in soil No information available.					
12.5. Results of PBT and The substances in the mix			ccording to REACH	l, annex XIII.	
12.6. Other adverse effer General regulation Harmful to aquatic life with lo Do not allow uncontrolled lea	ng lasting effects.	o the environment.			

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.



SECTION 13: Disposal considerations

13.1. Waste treatment met	hods
Waste code No.	Name of waste
08 04 12	adhesive and sealant sludges other than those mentioned in 08 04 11
15 01 02	plastic packaging

Recommendations for the product Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	3082	3082	3082
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N. O.S. (reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700))	Environmentally hazardous substance, liquid, n.o.s. (reaction product: bisphenol- A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700))
14.3. Transport hazard class(es)	9	9	9
14.4. Packing group	III	Ш	III
14.5. Environmental hazards	Yes	Yes	Yes
14.6. Special precautions for No information available.	user		
14.7. Transport in bulk accord not applicable	ding to Annex II of MARPOL	73/78 and the IBC Code	
Land and inland navigation to	ransport ADR/RID		

Hazard label(s) 9 tunnel restriction code E Classification code M6

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard VOC content 0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed. For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product. Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.2

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H411 Toxic to aquatic life with long lasting effects.



! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Name of product	Fast-Metal Minute Adhesive Hardener Code-Nr. 105512
1.2. Relevant identified uses of the substance or m Recommended intended purpose(s) 2-Component Epoxy Resin - Hardener Component	ixture and uses advised against
1.3. Details of the supplier of the safety data sheet	
Distributor	WEICON GmbH & Co. KG Königsberger Str. 255,, DE-48157 Münster Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244 E-Mail : msds@weicon.de Internet : www.weicon.de
Advice	Produktsicherheit / Product-Safety-Department Phone ++49(0)251 / 9322 - 0 E-mail (competent person): msds@weicon.de
1.4. Emergency telephone number	
	EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English) TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)
Manufacturer	WEICON GmbH & Co. KG Königsberger Str. 255, DE-48157 Münster
1.4. Emergency telephone number	
	GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h): Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Additional hints

This mixture is not classified as hazardous according to Regulation (EC) 1272/2008 [GHS].

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]

Special rules for supplemental label elements for certain mixtures

Safety data sheet available on request.

2.3. Other hazards

Information pertaining to special dangers for human and environment

Although this product is not subject to reporting requirements for hazardous products, we recommend compliance with the safety recommendations.



Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

Hardener for a 2-component epoxy adhesive

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
90-72-2	202-013-9	2,4,6-tris(dimethylaminomethyl)phenol	1 - 5	Acute Tox. 4, H302 / Eye Irrit. 2, H319 / Skin Irrit. 2, H315

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately and dispose it safely.

In case of inhalation

Ensure of fresh air. In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water. Consult a doctor if skin irritation persists.

In case of eye contact

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

In case of ingestion

Do not induce vomiting. Call for a doctor immediately. Rinse out mouth and give plenty of water to drink.

4.2. Most important symptoms and effects, both acute and delayed

Physician's information / possible symptoms

Coughing vomiting Respiratory complaints Headache Nausea skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

No information available.



SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Alcohol-resistant foam Dry fire-extinguishing substance Carbon dioxide Water spray jet

Unsuitable extinguishing media Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible. Carbon monoxide (CO) Carbon dioxide (CO2) Sulphur dioxide (SO2)

5.3. Advice for firefighters

Special protective equipment for fire-fighters Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus. Do not inhale explosion and/or combustion gases.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Ensure adequate ventilation. Use personal protective clothing. Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, sawdust, general-purpose binder). After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of aerosols. Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin Do not inhale gases/vapours/aerosols.



Hygiene measures

At work do not eat, drink and smoke. Remove soiled or soaked clothing immediately. Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities Requirements for storage rooms and vessels Keep in closed original container.

Advice on storage compatibility

Do not store with acids. Do not store together with animal feedstuffs. Do not store together with food.

Further information on storage conditions

Store at +5 till +25 °C. Keep container tightly closed and store at cool and aired place. Protect from frost. Protect from heat and direct solar radiation.

7.3. Specific end use(s)

Recommendation(s) for intended use See section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection Not required

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min **Eye protection**

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties					
Appearance	Colour	Odour			
liquid	yellowish-white	similar to ammonia			
Odour threshold					
not determined					
Important health, safety and	environmental information				

	Value	Temperature	at	Method	Remark
pH value	not determined				
Boiling temperature / boiling range	not determined				
Melting point / Freezing point	not determined				
Flash point	no				
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	not determined				
Self ignition temperature	not determined				
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	< 0,01 hPa				
Relative density	ca. 1,7				
Vapour density	not determined				
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	> 150 °C				
Viscosity	not determined				
Oxidising properties No information available.					



Explosive properties No information available.

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity No information available.

10.2. Chemical stability No information available.

Reactions with amines.

10.3. Possibility of hazardous reactions Reactions with strong oxidising agents.

10.4. Conditions to avoid Keep away from heat.

10.5. Incompatible materials

Substances to avoid Amines Oxidising agent, strong

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide. Toxic gases/vapours Sulphurous oxides (SOx)

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
Skin irritation	low irritant effect - not necessary to label			
Eye irritation	low irritant - no labeling duty			

Experiences made from practice

Frequent and / or prolonged contact may lead to skin irritation According to our experience and current information, the product has no detrimental effects on health if handled and used correctly

Additional information

The product is to be handled with the caution usual with chemicals. Other hazardous properties may not be excluded.



SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability Elimination rate

Method of analysis

nalysis

Method

Validation

not degradable

Biological degradability

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

08 04 12 15 01 02

Do not allow uncontrolled leakage of product into the environment. Product is not allowed to be discharged into aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods Waste code No.

Name of waste
adhesive and sealant sludges other than those mentioned in 08 04 11
plastic packaging

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazard	s -	-	-

14.6. Special precautions for user

No information available.



14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard VOC content

0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed. For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product. Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.2

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.