according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DOW CORNING(R) 3145 RTV MIL-A-46146

ADHESIVE/SEALANT-CLEAR

Product code : 00000000001190300

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Electrical industry and electronics, Adhesive, binding agents

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Dow Corning Europe S.A.

rue Jules Bordet - Parc Industriel - Zone C

B-7180 Seneffe

Telephone : English Tel: +49 611237507

Deutsch Tel: +49 611237500 Français Tel: +32 64511149 Italiano Tel: +32 64511170 Español Tel: +32 64511163

E-mail address of person

responsible for the SDS

sdseu@dowcorning.com

#### 1.4 Emergency telephone number

Dow Corning (Barry U.K. 24h) Tél: +44 1446732350 Dow Corning (Wiesbaden 24h) Tél: +49 61122158 Dow Corning (Seneffe 24h) Tel: +32 64 888240

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### **Additional Labelling**

EUH210 Safety data sheet available on request.

EUH208 Contains Methyltrimethoxysilane. May produce an allergic reaction.

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

#### 2.3 Other hazards

None known.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Silicone elastomer

#### **Hazardous components**

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
Methyltrimethoxysilane	1185-55-3	Flam. Liq. 2; H225	>= 1 - < 10
	214-685-0	Skin Sens. 1B; H317	
	01-2119517436-40		
Octamethylcyclotetrasiloxane	556-67-2	Flam. Liq. 3; H226	>= 0.1 - < 0.25
	209-136-7	Repr. 2; H361f	
	01-2119529238-36	Aquatic Chronic 4;	
		H413	
Dimethyldimethoxysilane	1112-39-6	Flam. Liq. 2; H225	>= 0.1 - < 0.3
	214-189-4	Repr. 2; H361f	
	01-2119976290-35	·	

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

when the potential for exposure exists.

If inhaled : If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

Version Revision Date: SDS Number: Date of last issue: 18.05.2016
1.8 17.10.2016 833617-00009 Date of first issue: 26.11.2014

Get medical attention.

Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

#### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides
Silicon oxides
Formaldehyde

Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Follow safe handling advice and personal protective equip-

ment recommendations.

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

#### 6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety

practice.

Keep away from water. Protect from moisture.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep in properly labelled containers. Store in accordance with

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

areas and containers the particular national regulations.

Advice on common storage : Do not store with the following product types:

Strong oxidizing agents

7.3 Specific end use(s)

Specific use(s) : These precautions are for room temperature handling. Use at

elevated temperature or aerosol/spray applications may re-

quire added precautions.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Methyltrimethox- ysilane	1185-55-3	TWA	7.5 ppm	DCC OEL
Octamethylcyclo- tetrasiloxane	556-67-2	TWA	10 ppm	US WEEL

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
Methanol	67-56-1	TWA	200 ppm	2006/15/EC
			260 mg/m3	
Further information	Indicative, Identifies the possibility of significant uptake through the skin			
		TWA	200 ppm	GB EH40
			266 mg/m3	
Further information	Can be absorbed through skin. The assigned substances are those for which			
	there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	250 ppm	GB EH40
			333 mg/m3	
Further information	Can be absorbed through skin. The assigned substances are those for which			
	there are concerns that dermal absorption will lead to systemic toxicity.			

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Methyltrimethoxysilane	Workers	Skin contact	Acute systemic effects	0.38 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	25.6 mg/m3
	Workers	Skin contact	Long-term systemic effects	0.38 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	25.6 mg/m3
	Consumers	Skin contact	Acute systemic ef-	0.3 mg/kg

according to Regulation (EC) No. 1907/2006



# DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

			fects	bw/day
	Consumers	Inhalation	Acute systemic effects	6.25 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0.26 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	0.3 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	6.25 mg/m3
	Consumers	Ingestion	Acute systemic ef- fects	0.26 mg/kg bw/day
Octamethylcyclotetra- siloxane	Workers	Inhalation	Acute systemic ef- fects	73 mg/m3
	Workers	Inhalation	Acute local effects	73 mg/m3
	Workers	Inhalation	Long-term systemic effects	73 mg/m3
	Workers	Inhalation	Long-term local ef- fects	73 mg/m3
	Consumers	Inhalation	Acute systemic effects	13 mg/m3
	Consumers	Inhalation	Acute local effects	13 mg/m3
	Consumers	Inhalation	Long-term systemic effects	13 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	13 mg/m3
	Consumers	Ingestion	Acute systemic effects	3.7 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	3.7 mg/kg bw/day
Methoxysilane	Workers	Skin contact	Acute systemic effects	7.44 mg/kg bw/day
	Workers	Inhalation	Acute systemic ef- fects	88.4 mg/m3
	Workers	Skin contact	Long-term systemic effects	7.44 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	88.4 mg/m3
	Consumers	Ingestion	Long-term systemic effects	5.21 mg/kg bw/day

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Methyltrimethoxysilane	Fresh water	>= 1.3 mg/l
	Marine water	>= 0.13 mg/l
	Fresh water sediment	>= 1.1 mg/kg
	Marine sediment	>= 0.11 mg/kg
	Soil	>= 0.17 mg/kg
	Sewage treatment plant	> 6.9 mg/l
Octamethylcyclotetrasiloxane	Fresh water	0.00044 mg/l
	Marine water	0.000044 mg/l
	Fresh water sediment	0.64 mg/kg
	Marine sediment	0.064 mg/kg

according to Regulation (EC) No. 1907/2006



## **DOW CORNING(R) 3145 RTV MIL-A-46146** ADHESIVE/SEALANT-CLEAR

Version Revision Date: SDS Number: Date of last issue: 18.05.2016 1.8 17.10.2016 833617-00009 Date of first issue: 26.11.2014

	Soil	0.13 mg/kg
	Sewage treatment plant	> 10 mg/l
Methoxysilane	Fresh water	0.24 mg/l
	Marine water	0.024 mg/l
	Fresh water sediment	0.22 mg/kg
	Marine sediment	0.022 mg/kg
	Soil	0.053 mg/kg
	Sewage treatment plant	10 mg/l

#### 8.2 Exposure controls

#### **Engineering measures**

Processing may form hazardous compounds (see section 10). Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

#### Personal protective equipment

Eye protection Wear the following personal protective equipment:

Safety glasses

Hand protection

Material Chemical-resistant gloves

Remarks Choose gloves to protect hands against chemicals depending

> on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the

end of workday.

Skin and body protection Select appropriate protective clothing based on chemical re-

sistance data and an assessment of the local exposure poten-

tial.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Use respiratory protection unless adequate local exhaust ven-Respiratory protection

tilation is provided or exposure assessment demonstrates that

exposures are within recommended exposure guidelines.

Self-contained breathing apparatus Filter type

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance paste

Colour white, translucent

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

Odour : slight

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Initial boiling point and boiling

range

Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : Not applicable

Relative vapour density : No data available

Relative density : 1.12

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weight : No data available

Self-ignition : The substance or mixture is not classified as pyrophoric. The

substance or mixture is not classified as self heating.

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Not classified as a reactivity hazard.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Use at elevated temperatures may form highly hazardous

compounds.

Can react with strong oxidizing agents.

When heated to temperatures above 180 °C (356 °F) in the presence of air, trace quantities of formaldehyde may be re-

leased.

Adequate ventilation is required.

Hazardous decomposition products will be formed upon con-

tact with water or humid air.

Hazardous decomposition products will be formed at elevated

temperatures.

10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

Water

10.6 Hazardous decomposition products

Contact with water or humid

Methanol

air

Thermal decomposition : Formaldehyde

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Information on likely routes of:

Skin contact Ingestion

exposure Ingest

Eye contact

**Acute toxicity** 

Not classified based on available information.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: On basis of test data.

**Components:** 

Methyltrimethoxysilane:

Acute oral toxicity : LD50 (Rat): 12.3 ml/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Information taken from reference works and the

literature.

Acute inhalation toxicity : LC50 (Rat): > 42.1 mg/l

Exposure time: 6 h Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: On basis of test data.

Acute dermal toxicity : LD50 (Rabbit): > 9,500 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: On basis of test data.

Octamethylcyclotetrasiloxane:

Acute oral toxicity : LD50 (Rat): > 4,800 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icitv

Remarks: On basis of test data.

Acute inhalation toxicity : LC50 (Rat): 2975 ppm

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: On basis of test data.

Acute dermal toxicity : LD50 (Rabbit): > 2.5 ml/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: On basis of test data.

Dimethyldimethoxysilane:

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg

Remarks: On basis of test data.

Acute inhalation toxicity : LC50 (Rat): > 4.7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: On basis of test data.

#### Skin corrosion/irritation

Not classified based on available information.

#### **Product:**

Species: Rabbit

Result: Mild skin irritation Remarks: On basis of test data.

#### **Components:**

#### Methyltrimethoxysilane:

Species: Rabbit

Result: No skin irritation

Remarks: On basis of test data.

#### Octamethylcyclotetrasiloxane:

Species: Rabbit

Result: No skin irritation

Remarks: On basis of test data.

#### Dimethyldimethoxysilane:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

#### Serious eye damage/eye irritation

Not classified based on available information.

#### **Product:**

Species: Rabbit

Result: No eye irritation

Remarks: On basis of test data.

#### **Components:**

#### Methyltrimethoxysilane:

Species: Rabbit

Result: No eye irritation

Remarks: On basis of test data.

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

Version Revision Date: SDS Number: Date of last issue: 18.05.2016 1.8 17.10.2016 833617-00009 Date of first issue: 26.11.2014

#### Octamethylcyclotetrasiloxane:

Species: Rabbit Result: No eye irritation

Remarks: On basis of test data.

#### **Dimethyldimethoxysilane:**

Species: Rabbit

Result: No eye irritation

Remarks: Based on data from similar materials

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### **Product:**

Assessment: Does not cause skin sensitisation.

Test Type: Buehler Test Species: Guinea pig Result: negative

Remarks: On basis of test data.

#### **Components:**

#### Methyltrimethoxysilane:

Assessment: Probability or evidence of low to moderate skin sensitisation rate in humans

Test Type: Buehler Test Species: Guinea pig Result: positive

Remarks: On basis of test data.

#### Octamethylcyclotetrasiloxane:

Assessment: Does not cause skin sensitisation.

Test Type: Maximisation Test

Species: Guinea pig Result: negative

Remarks: On basis of test data.

#### Germ cell mutagenicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

**Product:** 

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: On basis of test data.

**Components:** 

Methyltrimethoxysilane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: On basis of test data.

: Test Type: Mutagenicity (in vitro mammalian cytogenetic test)

Result: positive

Remarks: On basis of test data.

: Test Type: Chromosome aberration test in vitro

Result: positive

Remarks: On basis of test data.

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Result: negative

Remarks: On basis of test data.

Germ cell mutagenicity- As-

sessment

Animal testing did not show any mutagenic effects.

Octamethylcyclotetrasiloxane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: On basis of test data.

Test Type: Mutagenicity (in vitro mammalian cytogenetic test)

Result: negative

Remarks: On basis of test data.

Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: On basis of test data.

: Test Type: In vitro sister chromatid exchange assay in mam-

malian cells Result: negative

Remarks: On basis of test data.

: Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

Result: negative

Remarks: On basis of test data.

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: On basis of test data.

Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: On basis of test data.

Germ cell mutagenicity- As-

sessment

Animal testing did not show any mutagenic effects.

**Dimethyldimethoxysilane:** 

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: On basis of test data.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### **Components:**

#### Methyltrimethoxysilane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: Ingestion Symptoms: No effects on fertility Remarks: On basis of test data.

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: Ingestion

Symptoms: No effects on foetal development

Remarks: On basis of test data.

Reproductive toxicity - As-

sessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

#### Octamethylcyclotetrasiloxane:

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat, male and female Application Route: inhalation (vapour) Symptoms: Effects on fertility Remarks: On basis of test data.

Effects on foetal develop-

ment

Test Type: Prenatal development toxicity study (teratogenicity)

Species: Rabbit

Application Route: inhalation (vapour)
Symptoms: No effects on foetal development

Remarks: On basis of test data.

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on sexual function and

fertility, based on animal experiments.

Dimethyldimethoxysilane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: Ingestion Symptoms: Effects on fertility Remarks: On basis of test data.

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on sexual function and

fertility, based on animal experiments.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### **Components:**

#### Methyltrimethoxysilane:

Exposure routes: inhalation (vapour)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or

less.

Exposure routes: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg

bw or less.

#### Octamethylcyclotetrasiloxane:

Exposure routes: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg

bw or less.

Exposure routes: inhalation (vapour)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or

less.

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

Exposure routes: Skin contact

Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg

bw or less.

#### Dimethyldimethoxysilane:

Exposure routes: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg

bw or less.

#### Repeated dose toxicity

#### **Components:**

#### Methyltrimethoxysilane:

Species: Rat

Application Route: inhalation (vapour) Remarks: On basis of test data.

Species: Rat

Application Route: Ingestion Remarks: On basis of test data.

#### Octamethylcyclotetrasiloxane:

Species: Rat

Application Route: Ingestion Remarks: On basis of test data.

Species: Rat

Application Route: inhalation (vapour) Remarks: On basis of test data.

Species: Rabbit

Application Route: Skin contact Remarks: On basis of test data.

#### Dimethyldimethoxysilane:

Species: Rat

Application Route: Ingestion Remarks: On basis of test data.

#### **Aspiration toxicity**

Not classified based on available information.

#### **Further information**

#### **Components:**

#### Octamethylcyclotetrasiloxane:

Remarks: Results from a 2 year repeated vapour inhalation exposure study to rats of oc-

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

tamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

#### Dimethyldimethoxysilane:

Remarks: This material contains dimethyldimethoxysilane. Repeated exposure in rats to dimethyldimethoxysilane resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Components:**

#### Methyltrimethoxysilane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 110 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia sp. (water flea)): > 122 mg/l

Exposure time: 48 h

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 120

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : > 100 mg/l

Method: OECD Test Guideline 209

#### Octamethylcyclotetrasiloxane:

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): >

0.0063 mg/l

Exposure time: 336 h

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Mysidopsis bahia (opossum shrimp)): > 0.0091 mg/l

Exposure time: 96 h

Remarks: No toxicity at the limit of solubility

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): >

0.022 mg/l

Exposure time: 72 h

Remarks: No toxicity at the limit of solubility

Toxicity to fish (Chronic tox- : NOEC: >= 0.0044 mg/l

according to Regulation (EC) No. 1907/2006



## **DOW CORNING(R) 3145 RTV MIL-A-46146** ADHESIVE/SEALANT-CLEAR

Version Revision Date: SDS Number: Date of last issue: 18.05.2016 1.8 17.10.2016 833617-00009 Date of first issue: 26.11.2014

icity) Species: Oncorhynchus mykiss (rainbow trout)

> Remarks: On basis of test data. No toxicity at the limit of solubility

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOEC: >= 0.0079 mg/lExposure time: 21 d

Species: Daphnia magna (Water flea) Remarks: On basis of test data. No toxicity at the limit of solubility

**Ecotoxicology Assessment** 

Chronic aquatic toxicity May cause long lasting harmful effects to aquatic life.

Dimethyldimethoxysilane:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): > 126 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 119 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae EC50 (Pseudokirchneriella subcapitata (green algae)): > 118

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to microorganisms EC50 : > 100 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

#### 12.2 Persistence and degradability

#### Components:

#### Octamethylcyclotetrasiloxane:

Biodegradability Result: Not readily biodegradable.

Biodegradation: 3.7 % Exposure time: 28 d

Method: OECD Test Guideline 310

Degradation half life: 69.3 - 144 h (24.6 °C) Stability in water

pH: 7Method: OECD Test Guideline 111

Dimethyldimethoxysilane:

Degradation half life: < 0.6 h Stability in water

pH: 7

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.05.2016

 1.8
 17.10.2016
 833617-00009
 Date of first issue: 26.11.2014

#### 12.3 Bioaccumulative potential

#### **Components:**

#### Methyltrimethoxysilane:

Partition coefficient: n-

octanol/water

log Pow: -2.36

#### Octamethylcyclotetrasiloxane:

Bioaccumulation : Species: Pimephales promelas (fathead minnow)

Bioconcentration factor (BCF): 12,400

Partition coefficient: n-

octanol/water

log Pow: 6.48 (25.1 °C)

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Components:**

#### Octamethylcyclotetrasiloxane:

Assessment : Remarks: Octamethylcyclotetrasiloxane (D4) meets the cur-

rent REACh Annex XIII criteria for PBT and vPvB. In Canada, D4 has been assessed and deemed to meet the PiT criteria. However, D4 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D4 is not biomagnifying in aquatic and terrestrial food webs. D4 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D4 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living

organisms.

#### 12.6 Other adverse effects

No data available

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

Version Revision Date: SDS Number: Date of last issue: 18.05.2016
1.8 17.10.2016 833617-00009 Date of first issue: 26.11.2014

#### **SECTION 14: Transport information**

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

#### The components of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

REACH : For purchases from Dow Corning EU legal entities, all ingredi-

ents are currently pre/registered or exempt under REACH.

Please refer to section 1 for recommended uses. For pur-

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

Version Revision Date: SDS Number: Date of last issue: 18.05.2016
1.8 17.10.2016 833617-00009 Date of first issue: 26.11.2014

chases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representa-

tive/local office.

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from

inventory listing.

KECI : All ingredients listed, exempt or notified.

PICCS : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the Ca-

nadian Domestic Substances List (DSL).

TCSI : All ingredients listed or exempt.

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H317 : May cause an allergic skin reaction.
H361f : Suspected of damaging fertility.

H413 : May cause long lasting harmful effects to aquatic life.

#### Full text of other abbreviations

Aquatic Chronic : Chronic aquatic toxicity
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity
Skin Sens. : Skin sensitisation

2006/15/EC : Europe. Indicative occupational exposure limit values

DCC OEL : Dow Corning Guide

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

2006/15/EC / TWA : Limit Value - eight hours DCC OEL / TWA : Time weighted average

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

US WEEL / TWA : Time weighted average

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

Version Revision Date: SDS Number: Date of last issue: 18.05.2016
1.8 17.10.2016 833617-00009 Date of first issue: 26.11.2014

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road: AICS - Australian Inventory of Chemical Substances: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

Sources of key data used to compile the Safety Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

according to Regulation (EC) No. 1907/2006



# DOW CORNING(R) 3145 RTV MIL-A-46146 ADHESIVE/SEALANT-CLEAR

Version 1.8 Revision Date: 17.10.2016

SDS Number: 833617-00009

Date of last issue: 18.05.2016 Date of first issue: 26.11.2014

GB / EN