



Is Now Part of



**ON Semiconductor®**

To learn more about ON Semiconductor, please visit our website at  
[www.onsemi.com](http://www.onsemi.com)

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

# FDS8960C

## Dual N & P-Channel PowerTrench® MOSFET



### General Description

These dual N- and P-Channel enhancement mode power field effect transistors are produced using Fairchild Semiconductor's advanced PowerTrench process that has been especially tailored to minimize on-state resistance and yet maintain superior switching performance.

These devices are well suited for low voltage and battery powered applications where low in-line power loss and fast switching are required.

### Features

- **Q1:** N-Channel  
7.0A, 35V  $R_{DS(on)} = 0.024\Omega @ V_{GS} = 10V$   
 $R_{DS(on)} = 0.032\Omega @ V_{GS} = 4.5V$
- **Q2:** P-Channel  
-5A, -35V  $R_{DS(on)} = 0.053\Omega @ V_{GS} = -10V$   
 $R_{DS(on)} = 0.087\Omega @ V_{GS} = -4.5V$
- Fast switching speed
- RoHS compliant



### Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Q1	Q2	Units
$V_{DSS}$	Drain-Source Voltage	35	-35	V
$V_{DS(Avalanche)}$	Drain-Source Avalanche Voltage (maximum) (Note 3)	40	-40	V
$V_{GSS}$	Gate-Source Voltage	$\pm 20$	$\pm 25$	V
$I_D$	Drain Current - Continuous (Note 1a)	7	-5	A
	- Pulsed	20	-20	
$P_D$	Power Dissipation for Dual Operation	2		W
	Power Dissipation for Single Operation (Note 1a)	1.6		
	(Note 1b)	1		
	(Note 1c)	0.9		
$T_J, T_{STG}$	Operating and Storage Junction Temperature Range	-55 to +150		$^\circ\text{C}$

### Thermal Characteristics

$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (Note 1a)	78	$^\circ\text{C/W}$
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case (Note 1)	40	$^\circ\text{C/W}$

### Package Marking and Ordering Information

Device Marking	Device	Reel Size	Tape width	Quantity
FDS8960C	FDS8960C	13"	12mm	2500 units

### Electrical Characteristics

$T_A = 25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Units
--------	-----------	-----------------	------	-----	-----	-----	-------

#### Drain-Source Avalanche Ratings

$E_{AS}$	Drain-Source Avalanche Energy (Single Pulse)	$V_{DD} = 35\text{ V}, I_D = 7\text{ A}, L = 1\text{ mH}$	Q1			24.5	mJ
		$V_{DD} = -35\text{ V}, I_D = -5\text{ A}, L = 1\text{ mH}$	Q2			12.5	mJ
$I_{AS}$	Drain-Source Avalanche Current		Q1		7		A
			Q2		-5		

#### Off Characteristics

$BV_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_D = 250\text{ }\mu\text{A}$ $V_{GS} = 0\text{ V}, I_D = -250\text{ }\mu\text{A}$	Q1 Q2	35 -35			V
$\frac{\Delta BV_{DSS}}{\Delta T_J}$	Breakdown Voltage Temperature Coefficient	$I_D = 250\text{ }\mu\text{A}$ , Referenced to $25^\circ\text{C}$ $I_D = -250\text{ }\mu\text{A}$ , Referenced to $25^\circ\text{C}$	Q1 Q2		31 -40		$\text{mV}/^\circ\text{C}$
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS} = 28\text{ V}, V_{GS} = 0\text{ V}$	Q1			1	$\mu\text{A}$
		$V_{DS} = -28\text{ V}, V_{GS} = 0\text{ V}$	Q2			-1	
$I_{GSSF}$	Gate-Body Leakage, Forward	$V_{GS} = 20\text{ V}, V_{DS} = 0\text{ V}$	Q1			100	nA
$I_{GSSR}$	Gate-Body Leakage, Reverse	$V_{GS} = -20\text{ V}, V_{DS} = 0\text{ V}$				-100	nA
$I_{GSSR}$	Gate-Body Leakage, Forward	$V_{GS} = 25\text{ V}, V_{DS} = 0\text{ V}$	Q2			100	nA
$I_{GSSF}$	Gate-Body Leakage, Reverse	$V_{GS} = -25\text{ V}, V_{DS} = 0\text{ V}$				-100	nA

#### On Characteristics (Note 2)

$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\text{ }\mu\text{A}$	Q1	1	2	3	V
		$V_{DS} = V_{GS}, I_D = -250\text{ }\mu\text{A}$	Q2	-1	-1.8	-3	
$\frac{\Delta V_{GS(th)}}{\Delta T_J}$	Gate Threshold Voltage Temperature Coefficient	$I_D = 250\text{ }\mu\text{A}$ , Referenced to $25^\circ\text{C}$	Q1		-5		$\text{mV}/^\circ\text{C}$
		$I_D = -250\text{ }\mu\text{A}$ , Referenced to $25^\circ\text{C}$	Q2		4		
$R_{DS(on)}$	Static Drain-Source On-Resistance	$V_{GS} = 10\text{ V}, I_D = 7\text{ A}$	Q1		20	24	$\text{m}\Omega$
		$V_{GS} = 4.5\text{ V}, I_D = 6\text{ A}$			25	32	
		$V_{GS} = 10\text{ V}, I_D = 7\text{ A}, T_J = 125^\circ\text{C}$			29	37	
		$V_{GS} = -10\text{ V}, I_D = -5\text{ A}$	Q2		44	53	
$g_{FS}$	Forward Transconductance	$V_{DS} = 5\text{ V}, I_D = 7\text{ A}$	Q1		23		S
		$V_{DS} = -5\text{ V}, I_D = -5\text{ A}$	Q2		9		
		$V_{GS} = -4.5\text{ V}, I_D = -4\text{ A}$			70	87	
		$V_{GS} = -10\text{ V}, I_D = -5\text{ A}, T_J = 125^\circ\text{C}$			61	79	

#### Dynamic Characteristics

$C_{iss}$	Input Capacitance	Q1	Q1	570		$\text{pF}$
		$V_{DS} = 15\text{ V}, V_{GS} = 0\text{ V}, f = 1.0\text{ MHz}$	Q2	540		
$C_{oss}$	Output Capacitance	Q1	Q1	126		$\text{pF}$
		Q2	Q2	113		
$C_{rss}$	Reverse Transfer Capacitance	$V_{DS} = -15\text{ V}, V_{GS} = 0\text{ V}, f = 1.0\text{ MHz}$	Q1	52		$\text{pF}$
			Q2	60		
$R_G$	Gate Resistance	$f = 1.0\text{ MHz}$	Q1	2		$\Omega$
			Q2	6		

**Electrical Characteristics (continued)**  $T_A = 25^\circ\text{C}$  unless otherwise noted


Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Units
<b>Switching Characteristics</b> (Note 2)							
$t_{d(on)}$	Turn-On Delay Time	Q1 $V_{DD} = 15\text{ V}, I_D = 1\text{ A},$ $V_{GS} = 10\text{ V}, R_{GEN} = 6\ \Omega$	Q1 Q2		8 12	16 22	ns
$t_r$	Turn-On Rise Time		Q1 Q2		5 16	10 29	ns
$t_{d(off)}$	Turn-Off Delay Time	Q2 $V_{DD} = -15\text{ V}, I_D = -1\text{ A},$ $V_{GS} = -10\text{ V}, R_{GEN} = 6\ \Omega$	Q1 Q2		23 20	37 32	ns
$t_f$	Turn-Off Fall Time		Q1 Q2		3 5	6 10	ns
$Q_g$	Total Gate Charge	Q1 $V_{DS} = 15\text{ V}, I_D = 7\text{ A}, V_{GS} = 5\text{ V}$	Q1 Q2		5.5 5.7	7.7 8	nC
$Q_{gs}$	Gate-Source Charge	Q2	Q1 Q2		1.8 1.8		nC
$Q_{gd}$	Gate-Drain Charge	$V_{DS} = -15\text{ V}, I_D = -5\text{ A}, V_{GS} = -5\text{ V}$	Q1 Q2		1.8 2		nC

**Drain-Source Diode Characteristics**


$I_S$	Maximum Continuous Drain-Source Diode Forward Current		Q1 Q2			1.3 -1.3	A
$V_{SD}$	Drain-Source Diode Forward Voltage	$V_{GS} = 0\text{ V}, I_S = 1.3\text{ A}$ (Note 2) $V_{GS} = 0\text{ V}, I_S = -1.3\text{ A}$ (Note 2)	Q1 Q2		0.8 -0.8	1.2 -1.2	V
$t_{rr}$	Diode Reverse Recovery Time	Q1 $I_F = 7\text{ A}, d_{IF}/d_t = 100\text{ A}/\mu\text{s}$	Q1 Q2		20 17		nS
$Q_{rr}$	Diode Reverse Recovery Charge	Q2 $I_F = -5\text{ A}, d_{IF}/d_t = 100\text{ A}/\mu\text{s}$	Q1 Q2		10 5		nC

**Notes:**


1.  $R_{\theta JA}$  is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins.  $R_{\theta JC}$  is guaranteed by design while  $R_{\theta CA}$  is determined by the user's board design.



a)  $78^\circ\text{C/W}$  when mounted on a  $0.5\text{ in}^2$  pad of 2 oz copper



b)  $125^\circ\text{C/W}$  when mounted on a  $.02\text{ in}^2$  pad of 2 oz copper



c)  $135^\circ\text{C/W}$  when mounted on a minimum pad.

Scale 1 : 1 on letter size paper

2. Pulse Test: Pulse Width <  $300\mu\text{s}$ , Duty Cycle < 2.0%

3. BV(avalanche) Single-Pulse rating is guaranteed by design if device is operated within the UIS SOA boundary of the device.

### Typical Characteristics: Q1 (N-Channel)




Figure 1. On-Region Characteristics.




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 3. On-Resistance Variation with Temperature.




Figure 4. On-Resistance Variation with Gate-to-Source Voltage.




Figure 5. Transfer Characteristics.




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature.

### Typical Characteristics: Q1 (N-Channel)




Figure 7. Gate Charge Characteristics.




Figure 8. Capacitance Characteristics.




Figure 9. Maximum Safe Operating Area.




Figure 10. Single Pulse Maximum Power Dissipation.




Figure 11. Single Pulse Maximum Peak Current




Figure 12. Unclamped Inductive Switching Capability

### Typical Characteristics: Q2 (P-Channel)




Figure 13. On-Region Characteristics.




Figure 14. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 15. On-Resistance Variation with Temperature.




Figure 16. On-Resistance Variation with Gate-to-Source Voltage.




Figure 17. Transfer Characteristics.




Figure 18. Body Diode Forward Voltage Variation with Source Current and Temperature.

### Typical Characteristics: Q2 (P-Channel)




Figure 19. Gate Charge Characteristics.




Figure 20. Capacitance Characteristics.




Figure 21. Maximum Safe Operating Area.




Figure 22. Single Pulse Maximum Power Dissipation.




Figure 23. Single Pulse Maximum Peak Current





Figure 24. Unclamped Inductive Switching Capability



### Typical Characteristics



**Figure 25. Transient Thermal Response Curve.**

Thermal characterization performed using the conditions described in Note 1c.

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local  
Sales Representative