

**RoHS  
Compliant**



## Features


- IP67 waterproof 50Ω front-lock bulkhead connector
- Low loss high quality 1.37mm microcoax cable
- Double screened 1.32mm microcoax cable option
- Original Hirose U.FL connector
- Soldered and crimped connectors
- Recommended Hirose U.FL antenna interface solution on Gemalto M2M (Cinterion) 3G modules

## Mechanical Characteristics

Cable diameter (Max.)	: 1.37mm (options of 1.32mm double screened cable)
Cable bend radius (Min.)	: 16mm (for 1.37mm)
Temperature range	: -40°C to +90°C
Mating torque (Max.)	: 0.245 N-m
Cable lengths (standard)	: 100mm

## Electrical characteristic

Impedance (nominal)	: 50Ω
Capacitance (nominal)	: 3.43dB/m (at 3GHz); 5.13dB/m (at 6GHz)
Insulation resistance	: 500MΩ (Min.)
Dielectric Withstanding Voltage	: 60V AC (rms)



Dimensions : Millimetres

Item	Description
1	SMA B/H Jack Crimp Type for 1.37mm Cable (Nut × 1, Washer × 1)
2	Heat Shrink Tube F32 Ø2.5mm L = 10mm Colour : Black
3	Ø1.37mm Cable Tin Plated Colour : Black
4	U.FL-LP-088 Shell for 1.37mm Cable
5	U.FL-LP-088 Contact Terminal for Ø1.37mm Cable

## Part Number Table

Description	Part Number
RF / Coaxial Cable Assembly, U.FL Right Angle Plug, SMA Bulkhead Jack, 100mm, Black	R-132G7210100CC

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.