
KEMET Part Number: MPLC0730L3R3

(UPID0730L3R300)



Power, MPLC, 3300 nH, 20%



General Information		
Style:	SMD Chip	
Series:	MPLC	
Description:	Shielded, Surface Mount Inductor	
Features:	Large Current Inductors	
RoHS:	Yes	
Core:	Composite	

Dimensions	
Chip Size	3026
L	7.7mm MAX
W	6.7mm +/-0.2mm
Т	3mm MAX
LL	1.4mm NOM
G	3.2mm +/-0.1mm

Specifications	
Inductance:	3.3 uH (0.1 MHz)
Inductance Tolerance:	20%
Temperature Range:	-20/+120C
Shielded:	Yes
Current:	6500 mAmps (Isat, 20% Drop In Inductance), 5700 mAmps (Irms, 40C Rise By Self Heating)
DC Resistance:	30 mOhms

Packaging Specifications	
Packaging:	T&R, 380mm
Packaging Quantity:	1000

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

