

KEMET Part Number: T491B106K020AT
(B45196H4106K209)

Tantalum, MnO₂ Tantalum, T491, 10 uF, 10%, 20 V, 3528, SMD, MnO₂, Molded, 2 Ohms, 2.1mm



Dimensions

| Dimensions | |
|------------|-------------------|
| Footprint | 3528 |
| L | 3.5mm +/-0.2mm |
| W | 2.8mm +/-0.2mm |
| H | 1.9mm +/-0.2mm |
| T | 0.13mm REF |
| S | 0.8mm +0.2/-0.3mm |
| F | 2.2mm +/-0.1mm |
| A | 1.9mm MIN |
| B | 0.4mm +/-0.15mm |
| E | 2.2mm REF |
| G | 1.8mm REF |
| P | 0.5mm REF |
| R | 1mm REF |
| X | 0.1mm +/-0.1mm |

Packaging Specifications

| | |
|---------------------|------------|
| Weight: | 107.45 mg |
| Packaging: | T&R, 178mm |
| Packaging Quantity: | 2000 |

General Information

| | |
|--------------|--------------------------------|
| Dielectric: | MnO ₂ Tantalum |
| Style: | SMD Chip |
| Series: | T491 |
| Description: | SMD, MnO ₂ , Molded |
| RoHS: | Yes |
| Termination: | Tin |

Specifications

| | |
|------------------------|---|
| Capacitance: | 10 uF |
| Capacitance Tolerance: | 10% |
| Voltage DC: | 20 VDC (85C), 13.4 VDC (125C) |
| Temperature Range: | -55/+125C |
| Dissipation Factor: | 6% |
| Failure Rate: | N/A |
| Resistance: | 2 Ohms (100kHz) |
| Current: | 201 mAmps (25C), 180.9 mAmps (85C), 80.4 mAmps (125C) |
| Leakage: | 2 uAmps |