
KEMET Part Number: C0805C684Z4VACTU

(C0805C684Z4VAC7800)



Ceramic, Commercial-(CxxxxC), 0.68 uF, -20/+80%, 16 V, 0805, Y5V, SMD, MLCC, General Purpose, Class III



Dimensions		
L	2mm +/-0.2mm	
W	1.25mm +/-0.2mm	
Т	0.9mm +/-0.10mm	
S	0.75mm MIN	
В	0.5mm +/-0.25mm	

Packaging Specifications		
Packaging:	T&R, 180mm, Paper Tape	
Packaging Quantity:	4000	

General Information		
Style:	SMD Chip	
Series:	Commercial-(CxxxxC)	
Chip Size:	0805	
Description:	SMD, MLCC, General Purpose, Class III	
Features:	Class III	
RoHS:	Yes	
Termination:	Tin	
Marking:	No	
Failure Rate:	N/A	
Miscellaneous:	Note: Referee time for Y5V dielectric for this part number is 1000 hours	

Specifications	
Capacitance:	0.68 uF
Capacitance Tolerance:	-20/+80%
Voltage DC:	16 VDC
Temperature Range:	-30/+85C
Temperature Coefficient:	Y5V
Dissipation Factor:	7%
Aging Rate:	7% Loss/Decade Hour
Insulation Resistance:	147 MOhms
Dielectric Strength:	40 V

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

