

Würth Elektronik eiSos GmbH & Co. KG

EMC & Inductive Solutions

Max-Eyth-Straße 1 · 74638 Waldenburg · Germany

Tel. +49 (0) 79 42 945-0 · Fax +49 (0) 79 42 945-400

eiSos@we-online.de · www.we-online.de



Product/Process Change Notice (PCN)

- Major change
 Minor change

PCN #: PCN_IndUCF_20170501 Case
 Dimensions

Product Affected: WE-UCF

PCN Date: February 1st, 2017

Effective Date: May 1st, 2017

Contact: Product Management

Phone: +49 (0) 7942 - 945 5001

Fax: +49 (0) 7942 - 945 5179

E-mail: pcn.eisos@we-online.de

- Product Mark
 Date Code
 Packaging
 Others

Attachment: Yes No

Samples:

DESCRIPTION AND PURPOSE OF CHANGE:

With the aim of extended product applicability, Würth Elektronik will change the specification of the component. The mechanical dimensions will be adjusted in order to meet product reliability. The part itself remains unchanged. Electrical parameters will not be changed.

DETAIL OF CHANGE:

The following part numbers are affected by changes in the datasheet:

- 744290130
- 744290560
- 744290121
- 744290321
- 744290152
- 744290472
- 744290103
- 744290283
- 744290473
- 744290683
- 744290104

Würth Elektronik eiSos GmbH & Co. KG Sitz Waldenburg, Registergericht Stuttgart HRA 580801

Komplementär Würth Elektronik eiSos Verwaltungs-GmbH, Sitz Waldenburg, Registergericht Stuttgart HRB 581033 · Geschäftsführer Oliver Konz, Thomas Schrott

Bankverbindungen UniCredit Bank AG Stuttgart, Konto 322 620 136, BLZ 600 202 90, IBAN DE86 6002 0290 0322 6201 36, SWIFT/BIC HYVEDEMM473

USt.-IdNr. DE220618976

Würth Elektronik eiSos GmbH & Co. KG

EMC & Inductive Solutions

Max-Eyth-Straße 1 · 74638 Waldenburg · Germany

Tel. +49 (0) 79 42 945-0 · Fax +49 (0) 79 42 945-400

eiSos@we-online.de · www.we-online.de



BEFORE CHANGE:	AFTER CHANGE:												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 33%;"></th> <th style="width: 33%; text-align: center;">old specification</th> <th style="width: 33%; text-align: center;">new specification</th> </tr> </thead> <tbody> <tr> <td>total length (including pins)</td> <td style="text-align: center;">16.6 mm +/- 0.4 mm</td> <td style="text-align: center;">17.6 mm max.</td> </tr> <tr> <td>case length</td> <td style="text-align: center;">14.0 mm +/- 0.1 mm</td> <td style="text-align: center;">14.5 mm max.</td> </tr> <tr> <td>total height</td> <td style="text-align: center;">9.3 mm +/- 0.2 mm</td> <td style="text-align: center;">9.5 mm max.</td> </tr> </tbody> </table>		old specification	new specification	total length (including pins)	16.6 mm +/- 0.4 mm	17.6 mm max.	case length	14.0 mm +/- 0.1 mm	14.5 mm max.	total height	9.3 mm +/- 0.2 mm	9.5 mm max.	
	old specification	new specification											
total length (including pins)	16.6 mm +/- 0.4 mm	17.6 mm max.											
case length	14.0 mm +/- 0.1 mm	14.5 mm max.											
total height	9.3 mm +/- 0.2 mm	9.5 mm max.											
<p>RELIABILITY / QUALIFICATION SUMMARY: n/a</p>													
<p>DATA SHEET CHANGE: <input checked="" type="checkbox"/> Yes (drawing only) <input type="checkbox"/> No</p>													