

General Information

Extended Product Type:	S1-M3-25
Product ID:	1SAM201907R1103
EAN:	4013614400827
Catalog Description:	S1-M3-25 Power Infeed Block
Long Description:	S1-M3-25 3-phase power infeed block Flat, for MS116 / MS132, 25mm ² , Type E

Categories

Products » Low Voltage Products and Systems » Control Products » Manual Motor Starters » Manual Motor Starters Accessories

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369010
EAN:	4013614400827

Container Information

Package Level 1 Length:	245 mm
Package Level 1 Height:	38 mm
Package Level 1 Gross Weight:	0.45 kg
Package Level 1 EAN:	4013614488207
Package Level 1 Units:	10 piece
Package Level 1 Width:	59 mm

Dimensions

Product Net Height:	43.95 mm
Product Net Depth:	32 mm
Product Net Weight:	0.042 kg
Product Net Width:	43.8 mm

Technical

Rated Operational Current (I _e):	65 A
Degree of Protection:	IP20
Connecting Capacity Main Circuit:	Rigid 1x 6 ... 25 mm ² Flexible 1x 6 ... 16 mm ²
Tightening Torque:	Main Circuit 2.5 N·m
Wire Stripping Length:	Main Circuit 10 mm
Recommended Screw Driver:	Pozidriv 2 M3.5
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1
Product Name:	Power Infeed Block
Suitable For:	MS116 MS132
Suitable for Product Class:	Manual Motor Starter
Rated Operational Voltage:	690 V

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Ambient Air Temperature:	Operation -25 ... +70 °C Storage -50 ...+80 °C

Technical UL/CSA

Ampere Rating UL/CSA:	65 A
Connecting Capacity Main Circuit UL/CSA:	Stranded 1/2x 10 ... 4 AWG Flexible 1/2x 10 ... 6 AWG
Tightening Torque UL/CSA:	Main Circuit 22 in·lb
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V

Certificates and Declarations (Document Number)

Instructions and Manuals: 2CDC131011M6802
2CDC131034M6801
2CDC131022M6802

cUL Certificate: 1SAA963001-1701

Data Sheet, Technical Information: 1SBC100192C02-

Declaration of Conformity - CE: 1SAD938510-0056

GOST Certificate: 1SAA937000-2703

RoHS Information: 1SAA963003-4402

UL Certificate: 1SAA963001-1602

Classifications

E-nummer: 3112082

ETIM 4: EC002498 - Accessories for low-voltage switch technology

ETIM 5: EC002498 - Accessories for low-voltage switch technology

ETIM 6: EC002498 - Accessories for low-voltage switch technology

eClass: 7.0 27379201

Object Classification Code: X

