Product data sheet Characteristics

QO816L100RB LOAD Center QO MLO 240V 100A 1PH 8SP

Product availability: Stock - Normally stocked in distribution facility





Price*: 231.00 USD



Main

Product	Load Center
Marketing Trade Name	QO
Load center type	Main lugs
Line Rated Current	100 A
Number of spaces	8
Short Circuit Current Rating	10 kA
Maximum Number of Single Pole Circuits	16
Maximum Number of Tandem Breakers	8
Phase	1 phase
System Voltage	120/240 V AC

Complementary

Main		
Product	Load Center	
Marketing Trade Name	QO	
Load center type	Main lugs	
Line Rated Current	100 A	
Number of spaces	8	
Short Circuit Current Rating	10 kA	
Maximum Number of Single Pole Circuits	16	
Maximum Number of Tandem Breakers	8	
Phase	1 phase	
System Voltage	120/240 V AC	
Complementary	AWG 8 AWG 1 (aluminium/conner)	
Wire Size	AWG 8AWG 1 (aluminium/copper)	
Wire Size Enclosure Rating	NEMA 3R outdoor	
Wire Size Enclosure Rating Cover type	NEMA 3R outdoor Surface cover	
Wire Size Enclosure Rating Cover type Electrical Connection	NEMA 3R outdoor Surface cover Lugs	
Wire Size Enclosure Rating Cover type Electrical Connection Grounding Bar	NEMA 3R outdoor Surface cover Lugs Grounding bar (ordered separately)	
Wire Size Enclosure Rating Cover type Electrical Connection Grounding Bar Electrical Connection	NEMA 3R outdoor Surface cover Lugs Grounding bar (ordered separately) Lugs	
Wire Size Enclosure Rating Cover type Electrical Connection Grounding Bar Electrical Connection Wiring Configuration	NEMA 3R outdoor Surface cover Lugs Grounding bar (ordered separately) Lugs 3-wire	
Wire Size Enclosure Rating Cover type Electrical Connection Grounding Bar Electrical Connection Wiring Configuration Busbar Material	NEMA 3R outdoor Surface cover Lugs Grounding bar (ordered separately) Lugs 3-wire Tin plated aluminium busbar	
Wire Size Enclosure Rating Cover type Electrical Connection Grounding Bar Electrical Connection Wiring Configuration Busbar Material Enclosure Material	NEMA 3R outdoor Surface cover Lugs Grounding bar (ordered separately) Lugs 3-wire Tin plated aluminium busbar Welded galvannealed steel	
Wire Size Enclosure Rating Cover type Electrical Connection Grounding Bar Electrical Connection Wiring Configuration Busbar Material Enclosure Material Cover Finish	NEMA 3R outdoor Surface cover Lugs Grounding bar (ordered separately) Lugs 3-wire Tin plated aluminium busbar Welded galvannealed steel Baked enamel grey	
Wire Size Enclosure Rating Cover type Electrical Connection Grounding Bar Electrical Connection Wiring Configuration Busbar Material Enclosure Material Cover Finish Box Number	NEMA 3R outdoor Surface cover Lugs Grounding bar (ordered separately) Lugs 3-wire Tin plated aluminium busbar Welded galvannealed steel Baked enamel grey 2R	
Wire Size Enclosure Rating Cover type Electrical Connection Grounding Bar Electrical Connection Wiring Configuration Busbar Material Enclosure Material Cover Finish	NEMA 3R outdoor Surface cover Lugs Grounding bar (ordered separately) Lugs 3-wire Tin plated aluminium busbar Welded galvannealed steel Baked enamel grey	

Width	8.9 in (226 mm)
	··· (==- ······)

Ordering and shipping details

Category	00101 - QO 1PH LC,2-8CKT,NEMA 1,3R
Discount Schedule	DE3A
GTIN	00785901785750
Nbr. of units in pkg.	1
Package weight(Lbs)	9.7699999999996
Returnability	Υ
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1423 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Contraction Warranty		
Warranty period	18 months	