

USB-C to VGA Adapter Cable - 2m (6 ft.) - 1920x1200

Product ID: CDP2VGAMM2MB



This USB- C^{TM} to VGA adapter cable offers a convenient solution for directly connecting your DisplayPort over USB Type- C^{TM} device to your VGA monitor, television or projector.

The adapter supports a connection distance of up to 2 m (6 ft.) and works with USB-C devices that support DP alt mode, such as the MacBook, ChromeBook PixelTM and DellTM XPSTM models 15 and 13. It's also compatible with ThunderboltTM 3 ports.

Clutter-free installation

At 2 m (6 ft.) in length, the adapter cable delivers a direct connection between your USB-C device and your VGA monitor. This means you don't have to use additional adapters or cabling, which helps ensure a tidy and professional installation. For shorter installations, we also offer a 1 m (3 ft.) USB-C to VGA cable, enabling you to choose the right cable length for your custom installation needs.





Hassle-free connection with USB Type-C

The USB-C to VGA adapter cable is easy to connect, through the versatility and convenience of the USB Type-C port on your device. USB-C is a reversible connector, so it doesn't matter which way you plug it in, the adapter will always connect. This saves you the frustration of trying to insert it correctly when you're docking your computer to your workstation or office hot desk.

Crystal-clear picture quality

The adapter harnesses the video capabilities that are built into your USB Type-C connector to deliver video resolutions up to 1920x1200 and 1080p, providing full high-definition support for your high-resolution VGA monitors. it's a great accessory for multitasking on high-resolution VGA displays at home, in the office or other HD work environments.

The CDP2VGAMM2MB is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Note:

Your USB-C equipped device must support video (DP alt mode) to work with this adapter.



Data Sheet

Certifications, Reports and Compatibility











Applications

- Connect a USB Type-C computer to a VGA projector or display in your classroom, auditorium or boardroom
- Install at your home workstation or office hot desk to make your USB-C computer compatible with your VGA display

Features

- Reduce clutter with a compact 2 m (6 ft.) adapter cable
- Hassle-free connection with the reversible USB-C connector
- Crystal-clear picture quality with support for video resolutions up to 1920x1200 and 1080p
- Plug-and-play installation
- No power adapter required
- Thunderbolt 3 port compatible



Data Sheet

Environmental Humidity Operating Temperature Storage Temperature Characteristics Cable Length Product Height Product Length Product Weight Product Width Product Width Product Width Shipping (Package) Weight 1 - VGA (15 pin, High Density D-Sub) Male Output 2 - VOC (32°F to 158°F) 2 - VO°C (32°F to 158°F) 3 - VO°C (32°F to 158°F) 3 - VO°C (32°F to 158°F) 4 - VO°C to 80°C (14°F to 176°F) 5 - VO°C to 80°C (14°F to 176°F) 6 - VO°C to 80°C (14°F to 176°F) 6 - VO°C to 80°C (14°F to 176°F) 6 - VO°C to 80°C (1		Warranty	2 Years
Ports 1 Performance Maximum Analog Resolutions 1920×1200 or 1080p Supported Resolutions 1024×768 1280×720 (High-definition 720p) 1920×1200 Wide Screen Supported Yes Connector(s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - VGA (15 pin, High Density D-Sub) Male Output Environmental Humidity 5×90% RH (Non-condensing) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 80°C (14°F to 176°F) Physical Characteristics Cable Length 2 m [6.6 ft] Product Height 15 mm [0.6 in] Product Weight 132 g [4.7 oz] Product Width 34 mm [1.3 in] Packaging Information Shipping (Package) Weight 0.1 kg [0.3 lb]	Hardware	Converter Type	Cable Adapters
Performance Maximum Analog Resolutions Supported Resolutions 1024x768 1280x720 (High-definition 720p) 1920x1200 Wide Screen Supported Yes Connector(s) Connector A Connector B 1 - VSB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - VGA (15 pin, High Density D-Sub) Male Output Environmental Humidity Operating Temperature O°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 80°C (14°F to 176°F) Physical Characteristics Cable Length Product Height 15 mm [0.6 in] Product Length Product Weight 132 g [4.7 oz] Product Weight Ackaging Information Shipping (Package) Weight O1. kg [0.3 lb]		Output Signal	VGA
Supported Resolutions 1024x768		Ports	1
1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200	Performance	Maximum Analog Resolutions	1920x1200 or 1080p
Connector (s) Connector A Connector B 1 - VSB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - VGA (15 pin, High Density D-Sub) Male Output Environmental Humidity Operating Temperature O°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 80°C (14°F to 176°F) Physical Characteristics Cable Length Product Height 15 mm [0.6 in] Product Length Product Weight 132 g [4.7 oz] Product Width Packaging Information 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 5 ~90% RH (Non-condensing) 6 0°C to 70°C (32°F to 158°F) 8 lack Cable Length Product Length Product Height 15 mm [0.6 in] 16 in] 17 mm [0.6 in] 18 mm [1.3 in] Packaging Information 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 1 - VGA (15 pin, High Density D-Sub) Male Output 2 m [6.6 ft] 2 m [6.6 ft] 3 m [6.6 ft] 4 m [6.6 ft] 4 m [6.6 ft] 5 m [6.6 ft] 4 m [6.6 ft] 5 m [6.6 ft] 6 n [6.6 ft] 6 n [6.6 ft] 7 m [6.6 ft] 8 n [6.6 ft] 9 n [6.6 f		Supported Resolutions	1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p)
Connector B 1 - VGA (15 pin, High Density D-Sub) Male Output Environmental Humidity 5 ~ 90% RH (Non-condensing) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 80°C (14°F to 176°F) Physical Characteristics Cable Length Product Height 15 mm [0.6 in] Product Length Product Length 2000 mm [78.7 in] Product Weight 132 g [4.7 oz] Product Width Packaging Information Shipping (Package) Weight 0.1 kg [0.3 lb]		Wide Screen Supported	Yes
Humidity 5~90% RH (Non-condensing) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 80°C (14°F to 176°F) Physical Characteristics Cable Length 2 m [6.6 ft] Product Height 15 mm [0.6 in] Product Length 2000 mm [78.7 in] Product Weight 132 g [4.7 oz] Product Width 34 mm [1.3 in] Packaging Information Humidity 5~90% RH (Non-condensing) Storage Temperature 0°C to 70°C (32°F to 158°F) Black C18°C (14°F to 176°F) In formation Plackaging Shipping (Package) Weight 0°C to 80°C (14°F to 176°F) Black 2 m [6.6 ft] 15 mm [0.6 in] 178.7 in] 189.2 [4.7 oz] 190.3 lb]	Connector(s)	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 80°C (14°F to 176°F) Physical Characteristics Cable Length 2 m [6.6 ft] Product Height 15 mm [0.6 in] Product Length 2000 mm [78.7 in] Product Weight 132 g [4.7 oz] Product Width 34 mm [1.3 in] Packaging Information O°C to 70°C (32°F to 158°F) -10°C to 80°C (14°F to 176°F) -10°C to 80°F to 176°F to 176°F to 176°F to 176°F to 176°F to 176°F to 176°		Connector B	1 - VGA (15 pin, High Density D-Sub) Male Output
Storage Temperature -10°C to 80°C (14°F to 176°F) Physical Characteristics Cable Length 2 m [6.6 ft] Product Height 15 mm [0.6 in] Product Length 2000 mm [78.7 in] Product Weight 132 g [4.7 oz] Product Width 34 mm [1.3 in] Packaging Information Storage Temperature -10°C to 80°C (14°F to 176°F) Black 2 m [6.6 ft] 2 m [6.6 ft] 9 mm [0.6 in] 2000 mm [78.7 in] 10 1 2 2 g [4.7 oz] 10 1 2 g [4.7 oz] 10 1 kg [0.3 lb]	Environmental	Humidity	5~90% RH (Non-condensing)
Physical CharacteristicsAccent ColorBlackCable Length2 m [6.6 ft]Product Height15 mm [0.6 in]Product Length2000 mm [78.7 in]Product Weight132 g [4.7 oz]Product Width34 mm [1.3 in]Packaging InformationShipping (Package) Weight0.1 kg [0.3 lb]		Operating Temperature	0°C to 70°C (32°F to 158°F)
Characteristics Cable Length Product Height Product Length Product Length Product Weight Product Width O.1 kg [0.3 lb]		Storage Temperature	-10°C to 80°C (14°F to 176°F)
Product Height 15 mm [0.6 in] Product Length 2000 mm [78.7 in] Product Weight 132 g [4.7 oz] Product Width 34 mm [1.3 in] Packaging Information Package) Weight 0.1 kg [0.3 lb]	Physical Characteristics	Accent Color	Black
Product Length 2000 mm [78.7 in] Product Weight 132 g [4.7 oz] Product Width 34 mm [1.3 in] Packaging Information Package) Weight 0.1 kg [0.3 lb]		Cable Length	2 m [6.6 ft]
Product Weight 132 g [4.7 oz] Product Width 34 mm [1.3 in] Packaging Shipping (Package) Weight 0.1 kg [0.3 lb] Information		Product Height	15 mm [0.6 in]
Product Width 34 mm [1.3 in] Packaging Shipping (Package) Weight 0.1 kg [0.3 lb] Information		Product Length	2000 mm [78.7 in]
Packaging Shipping (Package) Weight 0.1 kg [0.3 lb] Information		Product Weight	132 g [4.7 oz]
Information		Product Width	34 mm [1.3 in]
What's in the Box Included in Package 1 - USB-C to VGA adapter cable	Packaging Information	Shipping (Package) Weight	0.1 kg [0.3 lb]
	What's in the Box	Included in Package	1 - USB-C to VGA adapter cable

Product appearance and specifications are subject to change without notice.