



TapeCase Ltd.
420 Northgate Parkway, Wheeling, IL 60090
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Double Coated Vinyl Foam Tape

VF Series

General Description

Closed cell vinyl foam carrier with acrylic adhesive. Good cushion, conformable, flexible, weather and solvent resistant with internal foam strength.

Applications

Because of its high strength and ability to conform well to irregular surfaces, this vinyl foam tape is excellent for mounting identification signs and nameplates outdoors. UV and solvent resistant, it's made of a closed cell PVC (polyvinyl chloride) foam with an acrylic adhesive blended into the foam surface on both sides. Tape has a paper liner.

Product Benefits

- Bonds surfaces
- Provides handling convenience
- Initial repositionability

Technical Data

TECHNICAL PROPERTIES	
Adhesive Type	High Tack Acrylic
Adhesive Carrier	Closed Cell Polyvinyl Chloride Foam
Density	20 lb/ft ³
Temperature Range	-20°F-150°F
Application Temperature	70°F-100°F
Tensile Strength	60 psi
Water and Humidity Resistance	Excellent
Shelf Life	18 months from DOM

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.