



TapeCase Ltd.
1982 Lunt Ave, Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Glow in the Dark Marking Tape

7550 Series

Product Description

Using the latest photoluminescent technology, 7550 is a flexible laminated film that absorbs and stores energy from ambient light. In the event of a power outage this tape is immediately visible, providing people with a clearly illuminated evacuation route. Because 7550 easily affixes to walls, handrails, columns, around doorframes, and along stairways and baseboards, it is ideal for your low-level emergency egress system.

Product Construction

Flexible laminated, printed film coated with permanent acrylic pressure-sensitive adhesive and backed by poly-coated release liner.

Typical Properties

Property	Characteristic
Thickness	0.010 +/- 10% (film/adhesive)
Color	White/Green (normal light conditions)
Illumination	High Visibility Yellow/Green
UV Stability	Excellent
Installation	Position, peel-off backing and apply to dry, non oily surface. Minimum application temperature is 50°F

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes