



TapeCase Ltd.
1982 Lunt Ave, Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Double Coated UPVC Tape

TC290

Product Description

TC290 is a UPVC film, double coated with an exceptionally high tack, high peel, acrylic adhesive. The product is supplied with a 60# kraft release liner.

Applications

- Product assembly
- Difficult bonding and splicing applications
- Lamination to EPDM rubber, plastics, glass and urethane foams

Product Benefits

- Exceptionally high tack and peel
- UPVC films allow conformability
- High adhesive mass provides excellent gap-filling properties
- Excellent resistance to environmental extremes
- Exhibits excellent adhesion to ether and ester foams
- Bonds well to rough or porous surfaces

Technical Properties

Property	Characteristics	
Total Thickness (mil)	8.5	
Adhesive Thickness (acrylic) (mil)	3.5	
Carrier Thickness (UPVC) (mil)	1.5	
Release Liner Thickness (mil)	3.5	
Adhesion to Steel	oz./in.	136
	(N/25mm)	37.8
Operating Temperature Range (F)	-20 to 200	

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes