



TapeCase Ltd.
1982 Lunt Ave, Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Single Coated Polyethylene Tape S134

Product Description

S134 is a heavy duty polyethylene backing, single coated with a synthetic rubber adhesive. The backing is stabilized to resist the effects of UV exposure. This tape is very conformable and maintains a watertight seal in all weather conditions. It is also residue free.

Applications

Masking of window and doors in stucco applications. Greenhouse repair. Architectural bagging. Shrink-wrapping applications.

Typical Physical Properties

Total Thickness	9.0 mils
Adhesive Thickness	3.5 mils

Adhesive Test Data

ADHESIVE TEST DATA

Peel Adhesion (PSTC 101 Mod.)
Initial to S.S. (20 min. @ RT)

Oz./Inch (N/25mm)
70 19

Backing Adhesion (PSTC 101 Mod.)
Initial to Backing Substrate (20 min. @ RT)

35 9.6

Tensile Strength (ASTM D-1000)

lbs./Inch (N/25mm)
22 96

Elongation

100%

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers..
2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.