



Title of Change:	Copper wire conversion for LA72910V/VL/14VL and Mold compound change for LA72910VL
Proposed first ship date:	28 March 2017
Contact information:	Contact your local ON Semiconductor Sales Office or <Hiroshi.Kojima@onsemi.com>
Samples:	Contact your local ON Semiconductor Sales Office
Additional Reliability Data:	Contact your local ON Semiconductor Sales Office or <Satoru.Fujinuma@onsemi.com>.
Type of notification:	This is a Final Product/Process Change Notification (FPCN) sent to customers. FPCNs are issued 90 days prior to implementation of the change. ON Semiconductor will consider this change accepted, unless an inquiry is made in writing within 30 days of delivery of this notice. To do so, contact <PCN.Support@onsemi.com>.
Change Part Identification:	Affected products will be identified with date code.
Change category:	<input type="checkbox"/> Wafer Fab Change <input checked="" type="checkbox"/> Assembly Change <input type="checkbox"/> Test Change <input type="checkbox"/> Other _____
Change Sub-Category(s):	<input type="checkbox"/> Manufacturing Site Change/Addition <input checked="" type="checkbox"/> Material Change <input type="checkbox"/> Datasheet/Product Doc change <input type="checkbox"/> Manufacturing Process Change <input type="checkbox"/> Product specific change <input type="checkbox"/> Shipping/Packaging/Marking <input type="checkbox"/> Other: _____
Sites Affected:	<input type="checkbox"/> All site(s) <input type="checkbox"/> not applicable <input checked="" type="checkbox"/> ON Semiconductor site(s) : ON Tarlac City, Philippines <input type="checkbox"/> External Foundry/Subcon site(s)
Description and Purpose:	
This Final Change Notification announces the following changes: <ul style="list-style-type: none"> ➤ Gold wire connecting chip and Lead will be changed to Copper wire. ➤ Mold resin of LA72910VL will be changed to be suitable for Copper wire. There is no change to the electrical characteristic performance for the affected products.	



Reliability Data Summary:

QV DEVICE NAME : LA72910VL
PACKAGE : SSOP16(225mil)

Test	Specification	Condition	Interval	Results
HTOL	EIAJ ED-4701/100	Tj=Tjmax, Vcc=Operatingmax	1000 hrs	0/22
THB*	EIAJ ED-4701/100	85°C, 85% RH, Vcc=recommended	1000 hrs	0/22
TC*	EIAJ ED-4701/100	Ta= -65°C to +150°C	100 cyc	0/22
AC*	EIAJ ED-4701-3	Ta=121°C ,RH=100% ,205kPa	50 hrs	0/22
HTSL	EIAJ ED-4701/200	Ta= 150°C	1000 hrs	0/22
RSH	EIAJ ED-4701/300	Ta = 255°C , 10 sec (peak 260°C)	2times	0/22

Note:
The test items with * mark are put into operation after the reflow soldering (at 255°C for 10seconds)

Electrical Characteristic Summary:

There is no change in the electrical performance. Datasheet specifications remain unchanged.

List of affected Standard Parts:

Part Number	Qualification Vehicle
LA72910V-TLM-H	LA72910VL-TLM-E

List of affected Customer Specific Parts:

NOTE: Please be informed that parts impacted by this PDN/PCN are Special/Customer specific parts, thus MPN & CPN info will be available to affected customers only by clicking the "Custom PCN for Selected Company Button" in the Document Analysis page of PCMS/PCN Alert.