





Electrical Characteristics:

Voltage Rating	: 115/250V AC
Current Rating	
A. At 115V AC	: 5A RMS Max.
B. At 250V AC	: 5A RMS Max.
Operating Frequency	: 50/60 Hz
Leakage Current	: Each Line To Ground
A. @115V AC 60Hz	: 0.25mA Max.
B. @250V AC 50Hz	: 0.45mA Max.
Hipot Rating (For One Minute)	
A. Line To Ground	: 2,250V DC
B. Line To Line	: 1,450V DC
Temperature Range	: -25°C To +100°C
Minimum Insertion Loss in dB	: (At 50Ω System)


Freq.MHz	0.01	0.05	0.1	0.15	0.5	1	5	10	30
Com. Mode dB	-	-	-	15	30	38	45	45	40
Dif. Mode dB	-	-	-	6	15	20	40	45	45

Physical Dimensions



Dimensions : Millimetres

Schematic



Part Number Table

Description	Part Number
EMI Power Line Filter, 5A	SPC20192

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.