



## Main

Range	TeSys
Product name	TeSys VARIO LS
Device short name	VLS3P
Product or component type	Switch body
Performance level	High performance
Poles description	3P
Contacts type and composition	3 NO
Network type	AC
Network frequency	50/60 Hz

## Complementary

Mounting support	Door
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	32 A at 55 °C
[Ithe] conventional enclosed thermal current	32 A
[Ie] rated operational current	25 A (AC-23A) at 500 V 25 A (AC-23A) at 690 V 32 A (AC-21A) at 400 V 32 A (AC-21A) at 500 V 32 A (AC-21A) at 690 V 32 A (AC-22A) at 400 V 32 A (AC-22A) at 500 V 32 A (AC-22A) at 690 V 32 A (AC-23A) at 400 V 32 A at 600 V according to UL 508
Rated operational power in W	22 kW at 690 V (AC-23A) 18.5 kW at 500 V (AC-23A) 15 kW at 400 V (AC-23A)

Intermittent duty class	Class 120 - 60 %
Making capacity	320 A at 690 V] (AC-23A) 48 A at 690 V] (AC-21A) 96 A at 690 V] (AC-22A)
[Icm] rated short-circuit making capacity	1128 A at 690 V
[Icw] rated short-time withstand current	800 A at 690 V during 1 s
Rated conditional short-circuit current	50 kA at 400 V - associated fuse 32 A gG
Breaking capacity	48 A at 690 V AC-21A 96 A at 690 V AC-22A 256 A at 690 V AC-23A
Mechanical durability	100000 cycles
Electrical durability	100000 cycles AC-21A
Connections - terminals	Power circuit : screw clamp terminals cable 16 mm <sup>2</sup> - cable stiffness: flexible - without cable end Power circuit : screw clamp terminals cable 10 mm <sup>2</sup> - cable stiffness: solid
Tightening torque	Power circuit : 1.8...2 N.m - on screw clamp terminals
Height	73 mm
Width	45 mm
Depth	78 mm
Product weight	0.135 kg
Colour	Grey

## Environment

Standards	IEC 60947-3 UL 508 CSA C22.2 No 14
Product certifications	GL
IP degree of protection	IP20 conforming to IEC 60529
Mechanical robustness	Vibrations 2...100 Hz Fc 0.7 g IEC 60068-2-6 Shocks 11 ms Ea 15 gn IEC 60068-2-27
Ambient air temperature for operation	-25...55 °C
Fire resistance	960 °C conforming to IEC 60695-2-11

## Ordering and shipping details

Category	21734 - TESYS VLS DISCONNECT SWITCHES
Discount Schedule	CP1
GTIN	00785901561224
Nbr. of units in pkg.	1
Package weight(Lbs)	0.4299999999999999
Returnability	Y
Country of origin	IT