# **Copper Foil Shielding**





# RoHS Compliant

## Description

The copper foil shielding sleeving is woven with copper foil monofilament, it is used in different electrical and industrial fields, where EMI shielding, excellent protection and lightweight properties are required. It is lighter and more flexible than tinned cooper braided sleeving, so it can be a perfect combination of economy and durability.

#### Application

It is widely used in communication system, electronic medical equipment, military equipment as well.

#### **Technical Data**

Material	: Copper Filament
Operating Temperature	: -40°C to +150°C
Standard Colour	: Tinned Colour
Other Features	: Resists gasoline and engine chemicals
Cutting Tool	: Scissors

## Part Number Table

Description	Nominal	Expanded Range		Packing	Part Number
	Size	Min.	Max.	Facking	Part Nulliber
Copper Foil Shielding	4mm	3mm	7mm	300m	PP001410

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for iss or damage resulting from any reliance on the Information or use of it (including liability or such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com

