

Desoldering Wire



RoHS
Compliant



Features

- Thumb-wheel design can ensure easy control on the desoldering wire feeding speed.
- With the stainless steel nozzle, the finger will not feel hot during operation.
- The desoldering wire is vacuum sealed inside to protect it from moisture and to prolong the life span of the product.
- The coating of flux provides dependable, long-lasting protection from oxidation.
- The desoldering wire design can simplify the desoldering of printed circuit board components, non-PC board applications, etc.
- Colour: Black

Part Number Table

Description	Desoldering Wire Size	Part Number
Desoldering Wire	0.5mm × 1.5 meters	DT000078
	1mm × 1.5 meters	DT000079
	1.5mm × 1.5 meters	DT000080
	2mm × 1.5 meters	DT000081
	2.5mm × 1.5 meters	DT000082
	3mm × 1.5 meters	DT000083
	3.5mm × 1.5 meters	DT000084

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell Limited 2016.

