## XU5M18MB230WK

photo-electric sensor - XU5 - diffuse - 90° - Sn 0.4m - 24..240VAC/DC - 1/2"



#### Main

Range of product	OsiSense XU	
Series name	General purpose single mode	
Electronic sensor type	Photo-electric sensor	
Sensor name	XU5	
Sensor design	Cylindrical M18	
Detection system	Diffuse	
Material	Metal	
Line of sight type	90° lateral	
Type of output signal	Discrete	
Supply circuit type	AC/DC	
Wiring technique	2-wire	
Discrete output function	1 NC	
Electrical connection	1 male connector 1/2"20 UNF, 3 pins	
Product specific application	-	
Emission	Infrared diffuse	
[Sn] nominal sensing distance	0.4 m diffuse	

## Buy online

#### Complementary

Complementary		
Enclosure material	Nickel plated brass	
Lens material	PMMA	
Maximum sensing distance	0.6 m	
Output type	Solid state	
Add on output	Without	
Status LED	1 LED (yellow) for output state	
[Us] rated supply voltage	24240 V AC/DC	
Supply voltage limits	20264 V AC/DC	
Residual current	< 1.5 mA (open state)	
Switching capacity in mA	10200 mA (to be used with 0.4 A quick-blow fuse in series with the load)	
Switching frequency	<= 25 Hz	
Voltage drop	6 V (closed state)	
Delay first up	< 300 ms	
Delay response	< 20 ms	
Delay recovery	< 20 ms	
Setting-up	Sensitivity adjustment	
Diameter	18 mm	
Length	110 mm	
Product weight	0.075 kg	
-		

## **Environment**

-2555 °C	
-4070 °C	
7 gn, amplitude = +/- 1.5 mm (f = 1055 Hz) conforming to IEC 60068-2-6	
30 gn (duration = 11 ms) conforming to IEC 60068-2-27	
IP67 conforming to IEC 60529	

## Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Will not be compliant	
REACh	Reference not containing SVHC above the threshold	

## Contractual warranty


<b>_</b>		
Warranty period	18 months	



# Product data sheet Dimensions Drawings

# XU5M18MB230WK

## **Dimensions**




## Product data sheet Connections and Schema

## XU5M18MB230WK


## Wiring Schemes

## Connector



1: Grounding 2: AC/DC 3: AC/DC

## 2-wire AC or DC




# Product data sheet Performance Curves

## XU5M18MB230WK

## **Detection Curves**

## Diffuse System



1: White 90% 2: Grey 18% Object 10 x 10 cm