
KEMET Part Number: C2225X102JZGACTU

(C2225X102JZGAC7800)



Ceramic, FlexTerm-(CxxxxX), 1000 pF, 5%, 2,500 V, 2225, C0G, SMD, MLCC, FT-CAP, Ultra-Stable



General Information	
Style:	SMD Chip
Series:	FlexTerm-(CxxxxX)
Chip Size:	2225
Description:	SMD, MLCC, FT-CAP, Ultra- Stable
Features:	FT-CAP, Ultra-Stable
RoHS:	Yes
Termination:	Flexible Termination
Marking:	No
Failure Rate:	N/A

Dimensions		
L	5.9mm +/-0.75mm	
W	6.4mm +/-0.4mm	
Т	1.6mm +/-0.20mm	
В	0.7mm +/-0.35mm	

Packaging Specifications		
Packaging:	T&R, 180mm, Plastic Tape	
Packaging Quantity:	1000	

Specifications	
Capacitance:	1000 pF
Capacitance Tolerance:	5%
Voltage DC:	2500 VDC
Dielectric Withstanding Voltage:	3,000 V
Temperature Range:	-55/+125C
Temperature Coefficient:	COG
Dissipation Factor:	0.1%
Aging Rate:	0% Loss/Decade Hour
Insulation Resistance:	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

