



Description

The product is printed board mounted DC output solid state relay. Compact size and high inrush current. Load voltage is 60V DC.

Features

- MOSFET output
- Low on-state resistance
- Opto-isolation
- Dielectric strength $\geq 2500\text{VACrms}$
- PCB mounted
- Load current is 20 Amps

Applications

Suitable for control and isolation between control signal and high current as interface, widely used in different kinds of DC motor, DC power supply, electromechanical device etc.

Technical Specification

Input Circuit

Control Voltage Range	: 3V DC to 10V DC
Min. Turn-On Voltage	: 3V DC
Min. Turn-Off Voltage	: 1V DC
Max. Input Current	: 15mA

Output Circuit

Load Voltage Range	: 0 ~ 60V DC
Transient Overvoltage	: 80Vpk
Maximum Surge Current [@10ms] (20A)	: 100A
Max. Turn-on Time	: 1ms
Max. Turn-off Time	: 1ms
Max. Off-State Leakage Current [@ Rated Voltage]	: 0.1mA
Max. On Resistance (20A)	: 3.6m Ω


General Information

Dielectric Strength (50/60Hz)	
Input/Output	: $\geq 2500\text{Vrms}$
Ambient Operating Temperature Range	: -30°C to +80°C
Ambient Storage Temperature Range	: -30°C to +100°C
Weight (Typical) (Quick Connection Terminal)	: 20g

Solid State Relay




Diagram



Dimensions : Millimetres

Thermal Curve



Part Number Table

Description	Part Number
SSR, 20A, 60V DC, 3-10V DC	MCKSL60D20-L

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com
www.farnell.com
www.newark.com

