


Tantalum, MnO2 Tantalum, Commercial Grade, T350, 100 uF, 10%, 10 V, Radial, Solid Tantalum, Conformal, Dipped, Lead Spacing = 5.08mm



| General Information | |
|---------------------|---|
| Dielectric: | MnO2 Tantalum |
| Style: | Radial |
| Series: | T350 |
| Description: | Radial, Solid Tantalum, Conformal, Dipped |
| Features: | Low Leakage |
| RoHS: | Yes |
| Termination: | Tin |
| Notes: | Longest Lead Is Positive |

| Dimensions | |
|------------|------------------|
| D | 8.4mm |
| H | 12.7mm |
| S | 5.08mm +/-0.38mm |
| LL | 12.7mm +/-1.26mm |
| F | 0.5mm +/-0.05mm |

| Specifications | |
|-------------------------------|--|
| Capacitance: | 100 uF |
| Capacitance Tolerance: | 10% |
| Voltage DC: | 10 VDC (85C), 9 VDC (125C Surge), 0.1 V (125C Reverse) |
| Temperature Range: | -55/+125C |
| Dissipation Factor: | 8% |
| Leakage Current: | 8 uAmps |

| Packaging Specifications | |
|----------------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 100 |