


Tantalum, MnO₂ Tantalum, Commercial Grade, T356, 2.2 uF, 10%, 50 V, Radial, Solid Tantalum, Conformal, Dipped, Lead Spacing = 5.08mm



| General Information | |
|---------------------|---|
| Dielectric: | MnO ₂ Tantalum |
| Style: | Radial |
| Series: | T356 |
| Description: | Radial, Solid Tantalum, Conformal, Dipped |
| Features: | Low Leakage, Reverse Voltage |
| RoHS: | Yes |
| Termination: | Tin |
| Notes: | Longest Lead Is Positive |

| Dimensions | |
|------------|------------------|
| D | 5.5mm |
| H | 10.2mm |
| S | 5.08mm +/-0.38mm |
| LL | 4.75mm +/-0.81mm |
| F | 0.5mm +/-0.05mm |

| Specifications | |
|-------------------------------|---|
| Capacitance: | 2.2 uF |
| Capacitance Tolerance: | 10% |
| Voltage DC: | 50 VDC (85C), 40 VDC (125C Surge), 0.5 V (125C Reverse) |
| Temperature Range: | -55/+125C |
| Dissipation Factor: | 5% |
| Leakage Current: | 0.9 uAmps |

| Packaging Specifications | |
|----------------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 1000 |