FIBOX
Enclosing innovations

UL CAB UL CAB PC 504020 G

Sample photo

Order symbol:	UL CAB PC 504020 G	**EAN**:	6418074011411
Product nbr:	8143360	**El. number**:	
Description:	UL Cabinet, PC	Finland:	
Remarks:	Latches on the long side, smooth	Electric No. Denmark:	8212034196
		Electric No. Italy:	7821055U

Including: Cabinet base, door with PUR gasket, latches, screws for mounting plate/DIN-rail and corner plugs.

Dimensions:	**Length**	**Width**	**Height**
mm:	500	400	200
inch:	19.7	15.7	7.9

Materials:	
Material:	Polycarbonate
Base colour:	RAL 7035 -light grey
Cover colour:	RAL 7035 -light grey
Gasket material:	EPDM

Temperatures:	
Temperature °C (short term):	-40 … 120 °C
Temperature °C (continuous):	-40 … 80 °C
Temperature °F (short term):	-40 … 250 °F
Temperature °F (continuous):	-40 … 175 °F

Rating:

Ingress Protection (EN 60529): IP65
Impact Resistance (EN 62262): IK08
Electrical insulation: Totally insulated
Halogen free (DIN/VDE 0472, Part 815): 1
UV resistance: UL 508
Flammability Rating: UL 746C 5"
UL Type:
Glow Wire Test (IEC 695-2-1) °C: 960

Certificates:

Germanischer Lloyd (GL)
Underwriters Laboratories
SGS Fimko
Lloyds Register of Shipping (LR)
UL Canada
Gost R

CAB 500x400x200











© Fibox Oy, Data subject to change without notice (printed: 12.7.2017)