

For more Information
please call

1-800-Belden1



General Description:

EPDM high temperature lead wire. 150°C EPDM wire is recommended for Class 130(B), 155(F) and also in some 180(H) systems. It's UL Recognized under Style 3374 as 150°C-600V Appliance Wiring Material. The CSA Listing, as a coil lead, is 125°C, 600V.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
1	18	16x30	TC - Tinned Copper

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Material	Min. Avg. Wall (in.)
EPDM - Ethylene Propylene Diene Monomer Rubber	0.045

Overall Insulation

Overall Cable

Overall Nominal Diameter: 0.141 in.

Mechanical Characteristics (Overall)

UL Temperature Rating: 125°C (UL AWM Style 3340), 125°C (UL AWM Style 3374), 150°C

Bulk Cable Weight: 12.750 lbs/1000 ft.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL Rating: 600 V, 150°C

CSA Rating: 600 V, 125°C

CSA Type: CL1254

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

6.000

Max. Operating Voltage - UL:

Voltage

600 V RMS (UL AWM Style 3340)

600 V RMS (UL AWM Style 3374)

Max. Recommended Current:

37118 Hook-up/Lead - UL AWM Style 3340 and 3374

Description	Current
Single conductor in free air @ 30C ambient	24 amps

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
37118 002500	500 FT	7.500 LB	RED	F	#18 STR EPDM 150C 600V
37118 0025000	5,000 FT	70.000 LB	RED	C I Z	#18STR EPDM 150C 600VRED
37118 005500	500 FT	7.500 LB	GREEN, DARK	F	#18STREPDM150C600VDGRN
37118 009500	500 FT	7.500 LB	WHITE	F	#18 STR EPDM 150C 600V
37118 0095000	5,000 FT	70.000 LB	WHITE	C I Z	#18STR EPDM 150C 600VWHT
37118 010500	500 FT	7.500 LB	BLACK	F	#18 STR EPDM 150C 600V
37118 0105000	5,000 FT	70.000 LB	BLACK	C I Z	#18STR EPDM 150C 600VBLK
37118 0135000	5,000 FT	70.000 LB	BLUE, DARK	C I Z	#18STREPDM 150C 600VDBLU

Notes:

C = CRATE REEL PUT-UP.

F = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'

I = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 200'

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 1 Revision Date: 03-20-2013

© 2017 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).