



Main

Range	TeSys
Product name	TeSys CASK
Product or component type	Control relay
Device short name	CA3SK
Contacting application	Control circuit
Utilisation category	AC-15 DC-13
Pole contact composition	2 NO
[Ue] rated operational voltage	≤ 690 V ≤ 400 Hz
Control circuit type	DC standard
Control circuit voltage	24 V DC

Complementary

[Ith] conventional free air thermal current	10 A at ≤ 55 °C
Associated fuse rating	10 A gL conforming to VDE 0660 10 A gL conforming to IEC 60947
[Ui] rated insulation voltage	690 V conforming to CSA C22.2 No 14 690 V conforming to BS 5424 690 V conforming to IEC 60947 690 V conforming to VDE 0110 group C 690 V conforming to UL 508
Mounting support	Plate Rail
Connections - terminals	Screw clamp terminals 2 cable(s) 1.5...4 mm ² - cable stiffness: solid Screw clamp terminals 1 cable(s) 1.5...6 mm ² - cable stiffness: solid Screw clamp terminals 1 cable(s) 0.5...6 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable(s) 0.35...6 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable(s) 0.35...1.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable(s) 0.35...2.5 mm ² - cable stiffness: flexible - without cable end
Tightening torque	0.8 N.m - on screw clamp terminals pozidriv No 1

Control circuit voltage limits	0.85...1.1 U _c at 50 °C operational 0.1...0.75 U _c at 50 °C drop-out
Operating time	4...6 ms coil de-energisation and NO opening 8...12 ms coil energisation and NO closing
Mechanical durability	10 Mcycles
Operating rate	1200 cyc/h
Inrush power in W	2.2 W at 20 °C
Hold-in power consumption in W	At 20 °C
Heat dissipation	2.2 W
Height	56 mm
Width	27 mm
Depth	55.5 mm
Product weight	0.132 kg

Environment

Standards	NF C 63-110 VDE 0660 IEC 60947 BS 5424
Product certifications	CSA UL
IP degree of protection	IP2x
Protective treatment	TC conforming to IEC 60068
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-50...70 °C
Operating altitude	2000 m without derating in temperature

Contractual warranty

Warranty period	18 months
-----------------	-----------