

ENGLISH MEASUREMENT VERSION

E605001 Cord Sets - DataTuff® CAT6A 600V AWM IP20 RJ45 Cord Set



For more Information please call

1-800-Belden1



General Description:

1 meter (3.3 ft.), Shielded with solid conductors (ref: Belden Bonded-Pair Cable 7953A). Cable Rating NEC: CMR. CEC: CMR FT4. 600V AWM Rated.

EU Directive 2002/95/EC (RoHS):	Yes			
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006 EUP 50			
MII Order #39 (China RoHS):				
tes (Overall)				
Notes: For additional information about this product, visit	our web site at http://www.belden.com			
ble				
Description:	4 pair, 23 AWG bare copper, Polyolefin Insulation, Bonded pairs, Overall Beldfoil® Shield, Industrial Grade PVC, Oil Res, Sun Res, CMR, FT4. 600V AWM Rated			
Part Number:	7953A			
Shielding:	Aluminum Foil-Polyester Tape			
Electrical Performance:	Category 6A			
Maximum Operating Voltage:	300 V RMS (600 V AWM Rated)			
Applicable Standards:	ANSI/TIA-568-C.2, ISO/IEC 11801, EtherNet/IP(tm) Specification, UL 1666 Riser			
nnectors				
Description:	RJ45 plugs Suitable for use in IP20 unsealed applications			
Sealing:	Suitable for IP20			
Connector Interface:	IEC 60603-7			
Shielding:	Hard Brass - Tin plated			
Electrical Performance:	Category 6A			
Maximum Operating Voltage:	300 V RMS			
Applicable Standards:	ANSI/TIA-568-C.2, ISO/IEC 11801, EtherNet/IP Specification			
sembly				
Part Number:	E605001			
Electrical Performance:	Category 6A			
Maximum Operating Voltage:	300 V RMS (600 V AWM Rated)			
Storage Temperature Range:	-40°C To +70°C			
Installation Temperature Range:	-10°C To +60°C			
Operating Temperature Range:	-10°C To +60°C			
Applicable Standards:	ANSI/TIA/EIA-568-C.2, ISO/IEC 11801, UL 1863 and CSA-22.2 No. 233			
Shielding:	Aluminum Foil-Polyester Tape			
Length:	1 meter (3.3 ft.)			

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
E605001 010S1	1 EA	0.137 LB	BLACK		CORDSET IP20 C6A FTP SO 1M BK

Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

E605001 Cord Sets - DataTuff® CAT6A 600V AWM IP20 RJ45 Cord Set

Revision Date: 06-17-2015 Revision Number: 0

© 2016 Belden, Inc All Rights Reserved

All Rights Reserved. Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information, and belief at the date of its publication. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this product bisclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.