# Product datasheet Characteristics

# XUB2BPBWM12R

photo-electric sensor - XUB - receiver - 90° - Sn 15m - 12..24VDC - M12



#### Main

IVIAIII		
Range of product	OsiSense XU	, u
Series name	General purpose single mode	7
Electronic sensor type	Photo-electric sensor receiver	
Sensor name	XUB	#
Sensor design	Cylindrical M18	
Detection system	Thru beam	
Material	Metal	
Line of sight type	90° lateral	:: 
Type of output signal	Discrete	5
Supply circuit type	DC	E
Wiring technique	3-wire	
Discrete output type	PNP	
Discrete output function	1 NC	9
Electrical connection	1 male connector M12, 4 pins	
Product specific application	-	2.
Emission	Infrared thru beam	
[Sn] nominal sensing distance	15 m thru beam need a transmitter XUB2BKSWM12T	

#### Complementary

Enclosure material	Nickel plated brass	
Lens material	PMMA	
Maximum sensing distance	20 m thru beam	
Output type	Solid state	
Add on output	Without	
Status LED	1 LED (yellow) for output state	
[Us] rated supply voltage	1224 V DC with reverse polarity protection	
Supply voltage limits	1036 V DC	

Switching capacity in mA	<= 100 mA (overload and short-circuit protection)
Switching frequency	<= 500 Hz
Voltage drop	1.5 V (closed state)
Current consumption	35 mA (no-load)
Delay first up	< 15 ms
Delay response	< 1 ms
Delay recovery	< 1 ms
Setting-up	Without sensitivity adjustment
Diameter	18 mm
Length	76 mm
Product weight	0.05 kg

### Environment

Product certifications	CE CSA UL	
Ambient air temperature for operation	-2555 °C	
Ambient air temperature for storage	-4070 °C	
Vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 1055 Hz) conforming to IEC 60068-2-6	
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27	
IP degree of protection	IP65 double insulation conforming to IEC 60529 IP67 double insulation conforming to IEC 60529 IP69K double insulation conforming to DIN 40050	

## Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0903 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	

#### Contractual warranty

Contraction Warranty	
Warranty period	18 months