Product datasheet Characteristics

XUK5ARCNL2

photo-electric sensor - XUK - diffuse - Sn 1m - 24..240VAC/DC - cable 2m



Main

Main		
Range of product	OsiSense XU	<u> </u>
Series name	General purpose single mode	÷
Electronic sensor type	Photo-electric sensor	
Sensor name	XUK	
Sensor design	Compact 50 x 50	
Detection system	Diffuse	<u></u>
Material	Plastic	5
Type of output signal	Discrete	in a hi
Supply circuit type	AC/DC	
Wiring technique	5-wire	
Discrete output function	1 C/O	
Electrical connection	Cable	
Cable length	2 m	<u></u>
Product specific application	-	
Emission	Infrared diffuse	. <u></u>
[Sn] nominal sensing distance	1 m diffuse	
		4

Complementary

PBT	
PMMA	
1.5 m diffuse	
Relay	
5 x 0.34 mm²	
PVC	
6 mm	
1 LED (green) for supply 1 LED (yellow) for output state	
	PMMA 1.5 m diffuse Relay 5 x 0.34 mm² PVC 6 mm 1 LED (green) for supply

[Us] rated supply voltage	24240 V AC/DC
Switching capacity in mA	3 A (cos φ = 1 for 0.5 million cycles at 1 operating cycle per second at 250 V)
Switching frequency	<= 20 Hz
Current consumption	<= 35 mA (no-load)
Power consumption in W	2 W AC
Delay first up	< 60 ms
Delay response	< 25 ms
Delay recovery	< 25 ms
Setting-up	Sensitivity adjustment
Electrical durability	500000 cycles, cos f = 1, 60 cyc/mn at 250 V
Depth	50 mm
Height	50 mm
Width	18 mm
Product weight	0.035 kg

Environment

Product certifications	Ecolab CE
Ambient air temperature for operation	-2555 °C
Ambient air temperature for storage	-4070 °C
Vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 1055 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27
IP degree of protection	IP65 double insulation conforming to IEC 60529

Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0841 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
Product environmental profile	Available	
	Product environmental	
Product end of life instructions	Available	
	🚰 End of life manual	

Contractual warranty

Warranty period	18 months