# Product datasheet Characteristics

## LX1FJ110

TeSys F - contactor coil - LX1FJ - 110...120 V AC 40...400 Hz



#### Main

Maii		ģ
Range	TeSys	
Product or component type	Contactor coil	į
Device short name	LX1FJ	5
Range compatibility	TeSys F LC1F Contactor	# #
Control circuit type	AC 40400 Hz	
Control circuit voltage	110120 V AC 40400 Hz	in a second seco
Average resistance	9.8 Ohm inrush at 20 °C 230 Ohm holding at 20 °C	in a siling
Inductance of closed circuit	1.35 H	
Product compatibility	LC1F400	
Operating time	4075 ms closing 100170 ms opening	To a series of the series of t
Mechanical durability	10 Mcycles	9
Operating rate	2400 cyc/h at <= 55 °C	

### Complementary

Coil technology	Without built-in suppressor module	4
Control circuit voltage limits	0.851.1 Uc at 55 °C operational 40400 Hz 0.30.5 Uc at 55 °C drop-out 40400 Hz	
Inrush power in VA	1075 VA at 20 °C (cos f 0.9) 40400 Hz	
Hold-in power consumption in VA	15 VA at 20 °C (cos f 0.3) 40400 Hz	
Heat dissipation	14 W at 40400 Hz	

#### Environment

Ambient air temperature for operation	> -555 °C	- 8
Product weight	1 kg	- 6

Warranty period

18 months