

## 1279P Coax - Mini Hi-Res Component Video Cable



For more Information  
please call

1-800-Belden1



### General Description:

25 AWG solid .018" tinned copper conductors, FFEP insulation, Duobond® foil plus a tinned copper interlocked serve shield (95% coverage), PVC inner jackets, PVC jacket.

### Usage (Overall)

Suitable Applications:

RGB Projectors, LCD Projectors, Video Distribution, Component Video, Graphic Displays, Special Effects Editing, Animation, Video Post Production, Home Theater, Offices, Boardrooms, Auditoriums, Teleconferencing, Theaters

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
5	25	Solid	TC - Tinned Copper	.018

Total Number of Conductors:

5

#### Insulation

Insulation Material:

Insulation Material	Dia. (in.)
FFEP - Foam FEP	0.074

#### Inner Shield

Inner Shield Material:

Layer #	Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
1	Duobond®	Tape	Aluminum Foil-Poly Tape-Aluminum	Lightly bonded to dielectric 100
2		Interlocked Serve	TC - Tinned Copper	95

#### Inner Jacket

Inner Jacket Material:

Inner Jacket Material	Nom. Dia. (in.)
PVC - Polyvinyl Chloride	0.111

Inner Jacket Color Code Chart:

Number	Color
1	Red
2	Green
3	Blue
4	Yellow
5	Black

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

Overall Nominal Diameter:

0.330 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

UL Temperature Rating: 60°C

Non-UL Temperature Rating: 75°C

Bulk Cable Weight: 60 lbs/1000 ft.

Max. Recommended Pulling Tension: 83 lbs.

Min. Bend Radius (Each Coax): 1.100 in.

Min. Bend Radius (Overall): 3.250 in.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	No
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Flame Test

UL Flame Test:	NFPA 262
CSA Flame Test:	FT6

### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

### Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	1279R

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

**Impedance (Ohm)**  
75

### Nom. Inductance:

**Inductance (µH/ft)**  
.087

### Nom. Capacitance Conductor to Shield:

**Capacitance (pF/ft)**  
16.8

### Nominal Velocity of Propagation:

**VP (%)**  
81

### Nominal Delay:

**Delay (ns/ft)**  
1.26

### Nom. Conductor DC Resistance:

**DCR @ 20°C (Ohm/1000 ft)**  
34

### Nom. Inner Shield DC Resistance:

**DCR @ 20°C (Ohm/1000 ft)**  
5.4

### Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1	0.50
5	1.2
50	3.8
100	5.2
200	7.1
400	10.0
750	14.3
1000	16.9
2250	25.5
3000	33.9

### Max. Operating Voltage - UL:

## 1279P Coax - Mini Hi-Res Component Video Cable

<b>Voltage</b>
300 V RMS

Max. Operating Voltage - Non-UL:

<b>Voltage</b>
300 V RMS

Minimum Return Loss:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
		5	850	20

### Sweep Test

Sweep Testing: 5 - 850 MHz

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1279P 0081000	1,000 FT	66.000 LB	GRAY	C	5 #25 FFEP SH FLRST FLRST
1279P 008250	250 FT	18.250 LB	GRAY	C	5 #25 FFEP SH FLRST FLRST
1279P 008500	500 FT	33.500 LB	GRAY	C	5 #25 FFEP SH FLRST FLRST
1279P 0101000	1,000 FT	66.000 LB	BLACK	C	5 #25 FFEP SH FLRST FLRST
1279P 010250	250 FT	18.250 LB	BLACK	C	5 #25 FFEP SH FLRST FLRST
1279P 010500	500 FT	33.500 LB	BLACK	C	5 #25 FFEP SH FLRST FLRST

**Notes:**  
C = CRATE REEL PUT-UP.

Revision Number: 5    Revision Date: 08-01-2013

© 2017 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.