Product datasheet Characteristics

XUB5BNANL2

photo-electric sensor - XUB - diffuse - Sn 0.6m - 12..24VDC - cable 2m



Main

Mani		
Range of product	OsiSense XU	<u>.</u>
Series name	General purpose single mode	<u> </u>
Electronic sensor type	Photo-electric sensor	
Sensor name	XUB	
Sensor design	Cylindrical M18	
Detection system	Diffuse	<u></u>
Material	Metal	
Line of sight type	Axial	. <u>.</u>
Type of output signal	Discrete	
Supply circuit type	DC	
Wiring technique	3-wire	
Discrete output type	NPN	<u>,</u>
Discrete output function	1 NO	<u></u>
Electrical connection	Cable	<u> </u>
Cable length	2 m	ـــــــــــــــــــــــــــــــــــــ
Product specific application	-	g
Emission	Infrared diffuse	9
[Sn] nominal sensing distance	0.6 m diffuse	i or

Complementary

Nickel plated brass	
PMMA	
0.8 m diffuse	
Solid state	
Without	
PvR	i
1 LED (yellow) for output state	
	PMMA 0.8 m diffuse Solid state Without PvR

[Us] rated supply voltage	1224 V DC with reverse polarity protection
Supply voltage limits	1036 V DC
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)
Switching frequency	<= 500 Hz
Voltage drop	1.5 V (closed state)
Current consumption	35 mA (no-load)
Delay first up	< 15 ms
Delay response	< 1 ms
Delay recovery	< 1 ms
Setting-up	Sensitivity adjustment
Diameter	18 mm
Length	76 mm
Product weight	0.055 kg

Environment

Product certifications	CSA	
	UL	
	CE	
Ambient air temperature for operation	-2555 °C	
Ambient air temperature for storage	-4070 °C	
Vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 1055 Hz) conforming to IEC 60068-2-6	
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27	
IP degree of protection	IP65 double insulation conforming to IEC 60529	
	IP67 double insulation conforming to IEC 60529	

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0847 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	

Contractual warranty

Warranty period	18 months