Product datasheet Characteristics

ZARB12W

12 relay outputs wired connection - cable gland



Main

Range of product	Harmony	_
Product or component type	Base station	-
Device short name	ZARB	
Product specific application	Material handling Hoisting applications	

Complementary

Main		
Range of product	Harmony	
Product or component type	Base station	
Device short name	ZARB	
Product specific application	Material handling Hoisting applications	
Complementary		
Cable entry	Cable gland	
Material	PC (polycarbonate)	
[Us] rated supply voltage	24240 V AC/DC	
Provided equipment	Internal antenna	
Nominal output current	0.54 A at 48 V AC conforming to IEC 60947-5-1	
Number of relays	12	
Relay type	Motion relay outputs (9 NO) Auxiliary relay outputs (3 NO)	
Safety outputs	2 NC relay outputs	
Switching capacity in VA	5 VA DC 26 VA AC	
Maximum switching current	6.8 mA	
Maximum switching voltage	240 V AC/DC (+ 20 %)	
Communication network type	Wireless : Bluetooth low energy	
Transmission frequency	2.4 GHz	
Maximum sensing distance	100 m in free field	
Response time	100 ms	
Number of channels	40	
Fixing mode	4 holes	
Electrical durability	100000 cycles	
Mechanical durability	1000000 cycles	
Service life	0< 10 yr	

Width	280 mm	
Height	305 mm	
Depth	100 mm	
Product weight	1.45 kg	

Environment

Vibration resistance	0.075 mm (f= 1055 Hz)
Shock resistance	15 gn at 11 ms
IP degree of protection	IP65
NEMA degree of protection	NEMA 4
Pollution degree	3
Electromagnetic compatibility	Resistance to radiated electromagnetic fields : 10 V/m class B conforming to IEC 61000-4-3 Resistance to electrostatic discharge : 4 kV class B (on contact) conforming to IEC 61000-4-2 Resistance to electrostatic discharge : 8 kV class B (in air) conforming to IEC 61000-4-2
Standards	IEC 61000-6-2
Radio agreement	ICASA ANATEL SRRC FCC RSS ARIB
Relative humidity	097 %
Ambient air temperature for operation	> -2570 °C
Ambient air temperature for storage	> -4070 °C
Product certifications	CE C-Tick UL EAC CSA KC
Environmental characteristic	RoHS compliant
-	

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1415 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	-
	Product environmental	
Product end of life instructions	Available	
	🚰 End of life manual	