SC-JB8-2



Products Low Voltage Products and Systems Connection Devices Terminal Blocks Accessories Short Circuit Bridges

General Information	
Extended Product Type:	SC-JB8-2
Product ID:	1SNK900652R0000
EAN:	3472599872967
Catalog Description:	SC-JB8-2 Short circuit bridges - Yellow
Long Description:	 Allow safe short-circuiting of Current Tranformers circuits, - Insulated, - Fully operated by screwdriver, - Short circuited fixed position secured thanks to AJS9 tightening, - Adapted h ook shape maintains the bridge on the terminal block in the non short-circuited position, - T he orange version can be used as fixed jumpers.

Additional Information

ABB Industrial IT Suite:	Control IT
Ambient Air Temperature:	Operation -55 +110 °C Storage -55 +110 °C
Ambient Temperature:	-5 +40 °C
Color:	Yellow
Country of Origin:	France (FR)
Customs Tariff Number:	85389099
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
EAN:	3472599872967
Rammability According to UL94:	V0
Function:	Short Circuit Bridges
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SNK160027C0201
Insulation Material:	Polyamide
Invoice Description:	SC-JB8-2 Short circuit bridges - Yellow
Minimum Order Quantity:	25 piece
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715
Object Classification Code:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Object Classification Code: Order Multiple:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715
	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715 X
Order Multiple:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715 X 25 piece
Order Multiple: Package Level 1 EAN:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715 X 25 piece 3472599872967
Order Multiple: Package Level 1 EAN: Package Level 1 Gross Weight:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715 X 25 piece 3472599872967 0.05 kg
Order Multiple: Package Level 1 EAN: Package Level 1 Gross Weight: Package Level 1 Height:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715 X 25 piece 3472599872967 0.05 kg 20 mm
Order Multiple: Package Level 1 EAN: Package Level 1 Gross Weight: Package Level 1 Height: Package Level 1 Length:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715 X 25 piece 3472599872967 0.05 kg 20 mm 170 mm
Order Multiple: Package Level 1 EAN: Package Level 1 Gross Weight: Package Level 1 Height: Package Level 1 Length: Package Level 1 Units:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715 X 25 piece 3472599872967 0.05 kg 20 mm 170 mm 25 piece
Order Multiple: Package Level 1 EAN: Package Level 1 Gross Weight: Package Level 1 Height: Package Level 1 Length: Package Level 1 Units: Package Level 1 Width:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715 X 25 piece 3472599872967 0.05 kg 20 mm 170 mm 25 piece 125 mm
Order Multiple: Package Level 1 EAN: Package Level 1 Gross Weight: Package Level 1 Height: Package Level 1 Length: Package Level 1 Units: Package Level 1 Width: Package Level 2 Gross Weight:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715 X 25 piece 3472599872967 0.05 kg 20 mm 170 mm 25 piece 125 piece 125 mm 1.000 kg
Order Multiple: Package Level 1 EAN: Package Level 1 Gross Weight: Package Level 1 Height: Package Level 1 Height: Package Level 1 Length: Package Level 1 Units: Package Level 1 Width: Package Level 2 Gross Weight: Package Level 2 Height:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715 X 25 piece 3472599872967 0.05 kg 20 mm 170 mm 25 piece 125 piece 125 mm 1.000 kg 130 mm
Order Multiple: Package Level 1 EAN: Package Level 1 Gross Weight: Package Level 1 Height: Package Level 1 Length: Package Level 1 Units: Package Level 1 Width: Package Level 2 Gross Weight: Package Level 2 Height: Package Level 2 Length:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715 X 25 piece 3472599872967 0.05 kg 20 mm 170 mm 25 piece 125 piece 130 mm 227 mm
Order Multiple: Package Level 1 EAN: Package Level 1 Gross Weight: Package Level 1 Height: Package Level 1 Height: Package Level 1 Length: Package Level 1 Units: Package Level 1 Width: Package Level 2 Gross Weight: Package Level 2 Height: Package Level 2 Length: Package Level 2 Units:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715 X 25 piece 3472599872967 0.05 kg 20 mm 170 mm 25 piece 125 piece 130 mm 227 mm 500 piece
Order Multiple: Package Level 1 EAN: Package Level 1 Gross Weight: Package Level 1 Height: Package Level 1 Height: Package Level 1 Length: Package Level 1 Units: Package Level 1 Width: Package Level 2 Gross Weight: Package Level 2 Height: Package Level 2 Length: Package Level 2 Units: Package Level 2 Width:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715 X 25 piece 3472599872967 0.05 kg 20 mm 170 mm 25 piece 125 piece 130 mm 227 mm 500 piece 175 mm

r rouuor name.	Short Shout Dhage
Product Net Depth:	13.9 mm
Product Net Height:	24.6 mm
Product Net Weight:	2 g
Product Net Width:	8 mm
Product Packing Type:	Bag
Rated Current (In):	Main Circuit 5 A
Recommended Screw Driver:	3.5 mm
RoHS Date:	18 08 2005
RoHS Information:	1SND230528F0200
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Spacing:	8 mm
Suitable For:	D6/8.ST.RS
	ZS10-PE-R1
	ZS10-R1
	ZS10-ST
	ZS10-ST-T4

