

Hazard Identification:

SAFETY DATA SHEET

Page 1 of 6 SDS-E-GX5S-6N

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 5.1

SDS Revision Date: 1/30/2016

1 Product Name:	DEOXIT® GOLD Gx-SERIES, 5% SPRAY, (P/N GX5S-6N), 163 grams				
	VOC Compliant				
2 Chemical Name:	NA NA				
.3 Synonyms:	DeoxIT® Gold Gx-Series 5% Spray; PN GX5S-6N				
.4 Trade Names:	DeoxIT® Gold Gx-Series 5% Spray; PN GX5S-6N				
.5 Product Uses & Restrictions:	Conditioner, enhancer for plated and gold plated electronic contacts & connectors				
.6 Distributor's Name:	CAIG Laboratories, Inc.				
.7 Distributor's Address:	12200 Thatcher Court, Poway, CA 92064-6876 USA				
.8 Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN XXXXX)				
.9 Business Phone / Fax:	+1 (800) 224-4123				

2. HAZARDS IDENTIFICATION

This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS

according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia).

DANGER! PRESSURIZED CONATINER; MAY BURST IF HEATED. EXTREMELY FLAMMABLE GAS.

Classification: Aerosols 1, Flam. Gas 1

Hazard Statements (H): H229 – Pressurized container; may burst if heated.

Precautionary Statements (P): P210 – Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. P251 – Do not pierce or burn, even after use. P410P412 – Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F

P332+P313 – If skin irritation occurs: get medical advice/attention. P377 – Leaking gas fire: Don not extinguish, unless leak can be stopped safely. P381 – In case of leakage, eliminate all ignition sources. P403 – Store in a well-ventilated place. P405 – Store locked up. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



3. COMPOSITION & INGREDIENT INFORMATION

					EXPOSURE LIMITS IN AIR (mg/m³)								
					AC	GIH		NOHSC			OSHA		
					pp	m		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
4 4 4 0 0 DENTAGULODODODANG	460-73-1	NA	419-170-6	60-100	300	NA	NF	NF	NF	NA	NA	NA	
1,1,1,3-3-PENTAFLUORPROPANE													
ISOBUTANE	75-28-5	TZ4300000	200-857-2	10-30	600	750	NF	NF	NF	NA	NA	NA	
130BUTANE	Press. Gas, Fla	am. Gas 1; H229,	H220										
DEOXIT® Gold Gx-SERIES,	NA	NA	NA	3-7	NA	NA	NF	NF	NF	NA	NA	NA	
GX100L	NO HAZARDO	US INGREDIENT	rs										•

4. FIRST AID MEASURES

			4. FIRST AID MEASURES
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Eyes:	Splashes are not likely; however, mist may cause irritation. If product gets in the eyes may cause irritation; flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally. If irritation persists repeat flushing. Get medical attention.
		Skin:	Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Treat for frostbite if necessary, be gently warming affected area. If irritation, redness or swelling persists, contact a physician immediately.
		Inhalation:	Remove victim to fresh air at once. If breathing difficult, administer oxygen. Gross overexposure may cause central nervous system depression, dizziness, confusion, incoordination, drowsiness, irregular heartbeat accompanied by a strange feeling in the chest, "heart thumping," apprehension, lightheadedness, weakness, fainting, loss of consciousness, and death.
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause nausea, vomiting and/or diarrhea.
		Eyes:	Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.
		Inhalation:	Gross overexposure may cause central nervous system depression, dizziness, confusion, incoordination, drowsiness, irregular heartbeat accompanied by a strange feeling in the chest, "heart thumping," apprehension, light-headedness, weakness, fainting, loss of consciousness, and death.
L			



7.3

Special Precautions:

SAFETY DATA SHEET

Page 2 of 6 SDS-E-GX5S-6N

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 1/30/2016 4. FIRST AID MEASURES - cont'd 4.3 Symptoms of Overexposure: Nausea, intestinal discomfort, vomiting and/or diarrhea. Ingestion: Overexposure in eyes may cause redness, itching and watering. Eyes: Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Frostbite Skin: like symptoms. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some individuals. Inhalation: Gross overexposure may cause central nervous system depression, dizziness, confusion, incoordination, drowsiness, irregular heartbeat accompanied by a strange feeling in the chest, "heart thumping," apprehension, light-headedness, weakness, fainting, loss of consciousness, and death. Acute Health Effects Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause 4.4 drowsiness, dizziness, headaches and nausea. Frostbite like effect to skin. 4.5 Chronic Health Effects: Overexposure may trigger asthma-like symptoms in some sensitive individuals. May also induce skin sensitization and respiratory hypersensitivity. Possible allergic dermatitis 4.6 Target Organs: Eyes, Skin, Respiratory System. 47 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the HEALTH 1 Aggravated by Exposure: target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 1 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES 5.1 Fire & Explosion Hazards: Level 1 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. This product is not flammable. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, Hydrogen Fluoride). Extinguishing Methods Water, Foam, CO₂, Dry Chemical. Use water spray to cool unopened containers. 5.3 Firefighting Procedures: Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Spills Equipment. Plastic or rubber gloves, respirator, eye protection and apron may be required for clean-up of large spills. Small Spills: Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product and place into a container for later disposal. Do not use water or a material such as "speedy dry" to soak up material. Sweep up material using non-sparking materials (e.g., plastic brooms, shovels, dustpans) and place into a plastic container or plastic liner within another container. Large Spills: Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Do not eat, drink or smoke when handling this product. Contents under pressure. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm water. 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct

sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical

damage. To avoid unintentional spraying keep cap in place when not in use.

Clean all spills promptly.



Page 3 of 6 SDS-E-GX5S-6N

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 5.1

SDS Revision Date: 1/30/2016

		8. EXPOSURE CO	NTROLS	& PERS	ONAI	_ PROT	ΓECT	ION		
8.1	Exposure Limits:	5. <u>1</u> 30311 <u>1</u>	ACGIH		NOHSC			OSHA		OTHER
	ppm (mg/m³)	CHEMICAL NAME(S)	TLV STEL	ES-TWA E	S-STEL	ES-PEAK	PEL	STEL	IDLH	
		ISOBUTANE	600 750	NF	NF	NF	NA	NA	NA	
8.2	Ventilation & Engineering Controls:	General mechanical (e.g., fa exhaust ventilation to effecti product. Ensure appropriate	veľy remove a	and prevent I	ouildup (of vapors	or mist	generat	ed fron	n the handling of this
8.3	Respiratory Protection:	No special respiratory protectionstances where dusts of this protection authorized by 29	No special respiratory protection is required under typical circumstances of use or handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or							
8.4	Eye Protection:	Avoid eye contact. None rec when handling or using large			ons of u	se. Safety	glasse	s could	be used	
8.5	Hand Protection:	None required under normal sensitive individuals. When his impervious plastic gloves.								
8.6	Body Protection:	No apron required when han eye wash stations and deluginvolving large quantities of the	e showers sh	ould be avai	lable. L	Jpon comp	letion o	f work a	activities	
		9. PHYSIC	AL & CHE	EMICAL	PROF	PERTIE	S			
9.1	Appearance:	Light yellow aerosol spray/mi	st							
9.2	Odor:	Ethereal / hydrocarbon odor								
9.3	Odor Threshold:	NA								
9.4	pH:	NA								
9.5	Melting Point/Freezing Point:	NA								
9.6	Initial Boiling Point/Boiling	15 °C (59 °F) - 1,1,1,3,3-Pent	afluoronronan	Δ						
	Range:	, ,	andoropropan	-						
9.7	Flashpoint:	NA								
9.8	Upper/Lower Flammability Limits:	NA								
9.9	Vapor Pressure:	50 +/-5 PSIG @ 20 °C								
9.10	Vapor Density:	NA								
9.11	Relative Density:	0.8								
9.12	Solubility:	Not soluble in water								
9.13	Partition Coefficient (log Pow):	NA								
9.14	Autoignition Temperature:	412 °C (774 °F) – 1,1,1,3,3-P	antafluaranran	ono						
9.15	Decomposition Temperature:	NA	entandoroprop	ane						
	' '									
9.16	Viscosity:	NA								
9.17	Other Information:	VOC content 268 g/L								
		10. S	TABILITY	& REA	CTIVI	TY				
10.1	Stability:	Stable under normal condition	ns; unstable wi	ith heat or co	ntaminat	ion.		·		
10.2	Hazardous Decomposition Products:	Change in color signifies expension.	osure to ultravi	iolet light or e	xceeding	g shelf life.	Will no	t degrad	le to un	stable products.
10.3	Hazardous Polymerization:	Will not occur.								
10.4	Conditions to Avoid:	Open flames, sparks, high he	at, incompatib	le substance:	s and dir	ect sunligh	t.			
10.5	Incompatible Substances:	Avoid extreme heat and igniti	on sources. St	ore away from	n oxidize	ers.				
		11. TOXI	COL OGIO	CAL INE	ORM A	ATION				
11.1	Routes of Entry:	Inhalation: YES				ES	Ī		Ingest	ion: YES
11.2	,									1.20
11.3	Toxicity Data: Acute Toxicity:	This product has NOT been to available for some of the come 1,1,1,3,3-Pentafluoropropage noted at 35,000 ppm, the three ppm. Acute Inhalation (rat): effect. Acute Inhalation (mou activity during exposure. Moderate irritation to eyes	ponents of the case of the ca	e product: nal (rabbit) – ction of cardi 200,000 ppm. 0 > 100,000	LD ₅₀ > 2 ac arrhyt No lett ppm. No	2,000 mg/k hmias in thality at 20 lethality a	g; Card ne prese 0,000 p t 100,00	liac Sen ence of i opm. Evi 00 ppm.	sitizatio njected dence Evide	n (dogs) – No effects adrenalin was 44,000 of transient anesthetic nce of transient under
	·	drowsiness, dizziness, heada	ches and naus	sea.				, , , , , , , , , , , , , , , , , , ,	a	c. vaporo can cause
11.4	Chronic Toxicity: Suspected Carcinogen:	This material may aggravate a No.	any pre-existin	g skin conditi	on (e.g.,	aermatitis).			
11.5										



Page 4 of 6

SDS-E-GX5S-6N SDS Revision: 5.1 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 1/30/2016 11. TOXICOLOGICAL INFORMATION – cont'd 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. This product is not reported to produce mutagenic effects in humans. Mutagenicity: Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. Irritancy of Product: 11.7 The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.8 Biological Exposure Indices ΝE Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There is no specific data available for this product. 12.2 Effects on Plants & Animals There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Products covered by this MSDS, in their original form, when disposed as waste, are considered non hazardous waste according to Federal RCRA regulations (40 CFR 261). Disposal should be in accordance with local, state and federal regulations. Dispose of in accordance with federal, state and local regulations. Special Considerations: California Waste Code: 331 13.2 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): UN1950. AEROSOLS. 2.1 (LTD QTY. IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) - until 12/31/2020 14.2 IATA (AIR): UN1950. AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L) IMDG (OCN): 143 UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 14.4 TDGR (Canadian GND): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE" ADR/RID (EU): 14.5 UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L) 14.6 SCT (MEXICO): 14.7 ADGR (AUS): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 15. REGULATORY INFORMATION 15.1 SARA Reporting This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements SARA Threshold Planning 15.2 There are no specific Threshold Planning Quantities for the components of this product. Quantity: TSCA Inventory Status: 15.3 The components of this product are listed on the TSCA Inventory **CERCLA Reportable Quantity** 15.4 NA (RQ): 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G, 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. 15. REGULATORY INFORMATION – cont'd 1,1,1,2-Tetrafluorethane can be found on the following state criteria lists: Minnesota Hazardous Substances List (MN) 15.7 State Regulatory Information: No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). 15.8 Other Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC: Isobutene: Flammable (F) Risk Phrases: (R) 12 - Extremely flammable. Safety Phrases: (S) 2-9-16 - Keep out of reach of children. Keep container in a well-ventilated place. Keep away from sources of ignition - No

smoking.



Page 5 of 6 SDS-E-GX5S-6N

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 5.1

SDS Revision Date: 1/30/2016

	16. OTHER INFORMATION						
16.1	Other Information:	DANGER! PRESSURIZED CONATINER; MAY BURST IF HEATED. EXTREMELY FLAMMABLE GAS. Use only as directed. Keep out of reach of children. Keep container in a well-ventilated place. Keep away from sources of ignition – No smoking. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.					
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.					
16.3	Disclaimer:	government regulations must be reviewed for Laboratories, Inc.'s knowledge, the informatic accuracy, suitability or completeness is not guar provided. The information contained herein results.	OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other or applicability to this product. To the best of ShipMate's & CAIG in contained herein is reliable and accurate as of this date; however, aranteed and no warranties of any type, either expressed or implied, are elates only to the specific product(s). If this product(s) is combined with the considered. Data may be changed from time to time. Be sure to				
16.4	Prepared for:	CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 Tel: +1 (800) CAIG-123 (244-4123) Fax: +1 (858) 486-8398 fax http://www.caig.com/	CAIG LABORATORIES, INC.				
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	ShipMate Dangerous Goods Training & Consulting				



Page 6 of 6 SDS-E-GX5S-6N

repared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 1/30/2016

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number				
EXPOSURE LIMITS IN AIR:					
ACGIH	American Conference on Governmental Industrial Hygienists				
С	Ceiling Limit				
ES	Exposure Standard (Australia)				
IDLH	Immediately Dangerous to Life and Health				
OSHA	U.S. Occupational Safety and Health Administration				
PEL	Permissible Exposure Limit				
STEL	Short-Term Exposure Limit				
TLV	Threshold Limit Value				
TWA	Time Weighted Average				

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide avvgen to the body


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE NAME OF THE PERSON OF THE	
D		THE STATE OF THE S	
Е			
F		THE STATE OF THE S	





















₹ Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit			
mg/m3	milligrams per cubic meter			
NA	Not Available			
ND	Not Determined			
NE	Not Established			
NF	Not Found			
NR	No Results			
ppm	parts per million			
SCBA	Self-Contained Breathing Apparatus			

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:					
Autoignition	Minimum temperature required to initiate combustion in air with no other				
Temperature	source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will				
	explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will				
	explode or ignite in the presence of an ignition source				

HAZARD RATINGS:

0	Minimal Hazard			
1	Slight Hazard			
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			
ACD	Acidic			
ALK	Alkaline			
COR	Corrosive			
₩	Use No Water			
OX	Oxidizer			
TREFOIL	Radioactive			



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals				
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal				
ppm	Concentration expressed in parts of material per million parts				
TD _{io} Lowest dose to cause a symptom					
TCLo	Lowest concentration to cause a symptom				
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects				
TC, TC _o , LC _{lo} , & LC _o					
IARC	International Agency for Research on Cancer				
NTP	National Toxicology Program				
RTECS	Registry of Toxic Effects of Chemical Substances				
BCF	Bioconcentration Factor				
TLm	Median threshold limit				
log Kow or log Koc	Coefficient of Oil/Water Distribution				

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	U.S. Department of Transportation				
TC	Transport Canada				
EPA	U.S. Environmental Protection Agency				
DSL	Canadian Domestic Substance List				
NOHSC National Occupational Health and Safety Commission (Australia)					
NDSL	Canadian Non-Domestic Substance List				
PSL	Canadian Priority Substances List				
TSCA	U.S. Toxic Substance Control Act				
EU	European Union (European Union Directive 67/548/EEC)				
WGK	Wassergefährdungsklassen (German Water Hazard Class)				
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System				

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

	(4)	(2)		\odot	(4)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

		R. C.	*		®	X	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond	A LANGE OF THE PARTY OF THE PAR				
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment