

# HyperLink Wireless 5.4 GHz 17 dBi 90 Degree Sector Panel Antenna Model: HG5417P-090

### **Applications**

- 5.4 GHz band applications
- Unlicensed European 5.4 GHz band applications
- IEEE 802.11a
- WiFi systems & WiMAX technology
- Radio Local Area Networks (RLAN) & Fixed Wireless Access Systems (FWA)

#### **Features**

- All weather operation
- 90 degree beam width
- Up/down tilt mounting bracket
- Light weight, compact size
- Integral N-Female connector



#### **Description**

#### **Superior Performance**

The HyperLink HG5417P-090 Sector Panel WiFi Antenna combines high gain with a wide 90° beam-width. It is a professional quality "cell site" antenna designed primarily for service providers in the 5.4GHz band.

#### **Rugged and Weatherproof**

This antenna features a heavy-duty plastic radome for all-weather operation. The HG5417P-090 antenna is supplied with a tilt and swivel mast mount kit. This allows installation at various degrees of incline for easy alignment.

#### **Ideal for Wireless Internet "Cell" Sites**

This RF antenna is an ideal choice for Wireless Internet Provider "cell" sites since the cell size can be easily determined by adjusting the down-tilt angle. Horizontal coverage is a full 90 degrees.



#### **Specifications**

## **Electrical Specifications**

Frequency	5470-5725 MHz
Gain	17 dBi
Polarization	Vertical
Horizontal Beam Width	90 Degrees
Vertical Beam Width	8 Degrees
Impedance	50 Ohm
Max. Input Power	100 Watts
Front to Back Ratio	> 25 dB
VSWR	< 1.5:1 avg.
Lightning Protection	DC Ground

## **Mechanical Specifications**

Connector	N-Female	
Radome Material	UV Resistant PVC	
Weight	4.35 lbs. (1.97 kg)	
Dimensions	17.9 x 4.7 x 2.9 in. (455.6 x 118.6 x 66.4 mm)	
Operating Temperature	-40° C to 85° C (-40° F to 185° F)	
Mounting	2 in. (50.8 mm) O.D. pipe max.	
Down tilt (Mech)	0 to 20 Degrees (Adjustable)	
RoHS Compliant	Yes	

## **Wind Loading**

Wind Speed (MPH)	Loading – Front	Loading - Side
100	28.6 lbs	14.6 lbs.
125	44.7 lbs.	22.9 lbs.

#### **RF Antenna Patterns**

