



## LEAK DETECTOR WATER BASED LEAK DETECTOR



**LEAK DETECTOR** is a water based formulation, developed, without the use of harmful solvents, silicones or oils, to allow the safe and easy detection of all gas and air leaks.

### APPLICATIONS

Highlights all leaks even under low pressure and proves invaluable in the gas, plumbing, heating, automotive, offshore, engineering and welding industries. Ideal for QC tests, maintenance and safety checks on:

- Pipework
- Joints
- Valves
- Couplings
- Air Lines
- Cylinders
- Air Brakes
- Regulators
- Screw Connections
- Exhaust
- Compressors
- Welding Seams
- Inflatable Equipment

The product remains stable and does not break down in use. Completely odourless and non-flammable. Leak Detector is quick and easy to use. It is suitable for use on compressed air and most industrial gases.

### FEATURES

- Meets the requirement of DIN 30657\*
- NSF P1 registered. No. 150402
- Meets the requirements of BS EN 14291:2004, and can be used for VOSA MOT testing
- DVGW registration number NG 5170 AS 0069\*
- Meets the requirements of MIL-L-25567\* of oxygen compatibility. Testing of oxygen systems must be done carefully, and product residues should not be allowed to build up
- Can be used with all types of gases:
  - Natural gas - oxygen - compressed air
  - Use on all types of refrigerants; Propane - LPG. Butane - nitrogen. Acetylene - carbon dioxide.
- Non-staining, non-corrosive, stable and 'safe in use'
- Safe for use on all surfaces
- Fitted with a 360° Spray System for all angle use, even upside down
- Water Based - Clean and safe in use
- Non-Flammable - Ensures safety in use



## **DIRECTIONS**

- Spray evenly over area to be tested
- Bubbles will appear at the precise location of the leak
- Product is water-based and should not come into contact with energised electrical equipment.
- If necessary (e.g. for oxygen systems) product residues can be washed away with water.

## **TECHNICAL DATA (aerosol)**

Appearance	:	Clear, colourless liquid
Odour	:	Odourless
Specific Gravity (@20°C)	:	1.00
Flash Point	:	Not flammable
Boiling Point	:	100°C
Freezing Point	:	0°C
pH	:	8.5
Surface Tension (@20°C)	:	28mN/m
Foam Stability (DIN 53902)	:	90%
Corrosion Test (DIN 30657)	:	Not corrosive
Solubility	:	Soluble in water, insoluble in solvents
Flammability	:	Non-Flammable
Packaging	:	400ml aerosol

## **STORAGE**

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

## **HEALTH AND SAFETY**

Health and Safety sheet available separately.

## **TECHNICAL SERVICE**

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

## **MISREPRESENTATION ACT 1967**

## **TRADE DESCRIPTIONS ACT 1968**

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Ltd, Wylds Road, Bridgwater, Somerset, TA6 4DD, UK.

Tel: +44 (0) 1278 727200

Fax: +44 (0) 1278 425644

Web: [www.ambersil.com](http://www.ambersil.com)

E-mail: [sales.uk@crcind.com](mailto:sales.uk@crcind.com)

Version: 2

Updated: April 2017