# **Piezo Buzzer**

# pro-**signal**

# RoHS Compliant

#### Features


- Piezo indicator with an internal drive circuit
- · Continuous tone buzzer with PCB pins
- Pin spacing is 17.5cm
- Sealed base
- Black in colour
- Audio device for use in a wide range of applications including timers, remote monitoring systems, security and safety products & household appliances

### Specifications

Housing Material	: ABS
Pin Material	: Red copper
Rated Voltage	: 12V DC
Operating Voltage	: 5 ~ 15V DC
Rated Current*	: ≤15mA
Sound Output at 10cm*	: ≥100dB
Resonant Frequency	: 3500 ±500Hz
Tone	: Continuous
Operating Temperature	: -20°C to +60°C
Storage Temperature	: -30°C to +70°C
Weight	: 8g

\*Value applying at rated voltage (DC)

### Diagram



Dimensions: Millimetres Tolerance: ±0.5mm

## Part Number Table

Description	Part Number
Piezo Buzzer, 5-15V DC, 100dB, 15mA	ABI-022-RC

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage resulting from any reliance on the Information or use of it (including liability resulting from its negligence. pro-SIGNAL is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

