

## Features

- Electro mechanical, surface mount buzzer
- The sound opening is on the side of the buzzer rather than the top
- Black in colour
- Wave solderable, not washable
- Small and compact, this low profile buzzer is suitable for applications where space is limited


## Specifications

Lead pin Material	: Red copper (DSn)
Rated Voltage (Vp-p square wave)	: 3Vp-p
Operating Voltage	: 2Vp-p ~ 4Vp-p
Rated Current*	: ≤100mA
Sound Output at 3000Hz at 10cm*	: ≥85dB
Resonant frequency*	: 2731 Hz
Coil Resistance	: 15 ±3Ω
Operating Temperature	: -30°C to +70°C
Storage Temperature	: -40°C to +85°C
Weight	: 0.7g

\*Value applying at rated voltage (AC)

Requires additional electronic circuitry to operate as a sounder

## Diagram



1. Coil part - Copper and Iron
2. Diaphragm - Iron
3. Csse - LCP
4. Magnet- Ferrite
5. Cover - LCP

Dimensions: Millimetres

Tolerance: ±0.5mm

## Part Number Table

Description	Part Number
Electro Mech Buzzer, SMD, 2-4VP-P, 85dB	ABT-461-RC

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-SIGNAL is the registered trademark of the Group. © Premier Farnell Limited 2016.