Product data sheet Characteristics

NSYCRN88300

Spacial CRN plain door w/o mount.plate. H800xW800xD300 IP66 IK10 RAL7035...



Main

TTT COLUMN		·
Range	Spacial	
Product name	Spacial CRN	į
Device application	Multi-purpose	
Product or component type	Compact enclosure	
Enclosure nominal height	800 mm	
Enclosure nominal width	800 mm	3
Enclosure nominal depth	300 mm	
Installation accessory type	Wall-mounting	4 4 4 1
Device composition	Lock 1 Door 1 Body 1 Cable gland plate 2 bottom	A A A A A A A A A A A A A A A A A A A
Door type	Plain	7
Mounting plate description	Without mounting plate	
		9

Complementary

Complementary		S
Variant particularity	Back welded with double profile forming a protected sealed area Sides made from a single folded section	, ()
Number of doors	1 front face	
Door opening side	Reversible 120 °	
Lock type	3 mm double-bar lock	
Type of gland plate	Standard	
Accessibility for operation	Front	<u>5</u> .
Removable parts	Door by hinges Cable gland plate by screws	citati
Material	Steel for body	
Surface finish	Epoxy-polyester powder	<u>۔ ۔ ۔ ۔ ۔ ۔ ۔ ۔ ۔ ۔ ۔ ۔ ۔ ۔ ۔ ۔ ۔ ۔ ۔ </u>
Colour	Grey RAL 7035	
Standards	IEC 62208	

Product certifications	CUL	
	UL	
Environment		
IP degree of protection	IP66 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
Offer Sustainability		
Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
	Product environmental	
Product end of life instructions	Need no specific recycling operations	
Contractual warranty		
Warranty period	18 months	