

Surface Mount Fuse Slow Blow

PRODUCT: 0603SFS100F/32

DOCUMENT: SCD26398 PCN: RF0335-000 REV LETTER: D

REV DATE: JULY 26, 2016

PAGE NO.: 1 OF 2

Specification Status: Released

Max Electrical Rating at 25°C

Max Voltage: 32V_{DC}
Max Interrupt Current: 40A

Termination Material: Silver, Nickel, Tin

Fuse Element: Silver

Body Material: Glass Ceramic




TABLE I. DIMENSIONS:

	Α		В		С		D	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
mm:	1.45	1.75	0.65	0.95	0.21	0.51	0.65	0.95
in:	0.057	0.069	0.026	0.037	0.008	0.020	0.026	0.037

TABLE II. PERFORMANCE RATINGS @ 25°C (unless otherwise noted):

			OPER	ATING			
			TEMPERATURE (°C)				
RATED	NOMINAL COLD	100% of rated	200% of rated	300% of rated	800% of rated		
CURRENT (A)	DCR (Ω)*	current	current	current	current		
						MIN	MAX
						IVIIIN	IVIAX
			1 second min	0.1 second min	0.0005 second min		
1.0	0.200	4 hours min	120 seconds max	3 seconds max	0.05 seconds max	-55	125
	•	00	·	•			•

^{*} Measured at 10% of rated current and 25°C

Agency Recognition: UL E197536

Precedence: This specification takes precedence over documents referenced herein.

Effectivity: Reference documents shall be the issue in effect on the date of invitation for bid.

Materials Information

ROHS Compliant

ELV Compliant

Directive 2002/95/EC Compliant

Directive 2000/53/EC Compliant



Surface Mount Fuse Slow Blow

PRODUCT: 0603SFS100F/32

DOCUMENT: SCD26398 PCN: RF0335-000 REV LETTER: D

REV DATE: JULY 26, 2016

PAGE NO.: 2 OF 2

Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining, nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation. The sale and use of Littelfuse products is subject to Littelfuse Terms and Conditions of Sale, unless otherwise agreed by Littelfuse.