

NEW
THE POWER OF PING

PINGER *PLUS+*™

NETWORK IP TEST TOOL

VERIFIES CONNECTIVITY ACROSS A LAN OR WAN

FULL 10/100 Mbs PING CAPABILITY

- Detect Speed and Duplex of 10/100/1000 baseTX Links
- Verify IP Address Assignment with the DHCP Client Test
- Test Connectivity Across a LAN / WAN by Transmitting/Receiving Pings
- Measure Packet Response Time to Determine Network Performance
- Capture the MAC Address of an IP Address
- Transmit Link Activation Signals for Port Identification
- Store Multiple Profiles Consisting of Source / Destination IP Address, Gateway Address and Subnet Mask
- Configure from a Web Browser or Direct Keypad Entry



PINGER *PLUS+*™ Network IP Test Tool

Network maintainers commonly run PING tests from laptop computers to verify connectivity when troubleshooting a problem. PINGER *PLUS+*™ replaces expensive and fragile laptop computers with an affordable and rugged test device. PINGER *PLUS+*™ incorporates four new major test functions: 10/100/1000 baseTX Link identification; 10/100 PING capability; eight programmable profiles (Source and Destination IP addresses, Gateway IP address and Subnet Mask); and setup from a web browser. PINGER *PLUS+*™ provides a comprehensive array of PING test capabilities that include PINGing a prestored list of IP addresses, PINGing a range of IP addresses, continuously PING an IP address up to 99 times and vary the PING packet length. PINGER *PLUS+*™ is a highly advanced test tool that fits in a shirt pocket.



Applications

The *PINGER PLUS+*™ is an ideal tool for quickly testing proper LAN operation after completing a Move, Add or Change (MAC). Trouble Calls are easily handled by verifying Link connection and running the comprehensive PING test. Resolve the "I can not connect to the Internet" problem with DHCP Client mode that ensures a DHCP Server is available and display the assigned IP Address. Remote Office Support can be provided by connecting the *PINGER PLUS+*™ to the LAN at the remote office trouble point and then PING the unit over the Internet or Intranet.

Verify end-to-end operations prior to installing workstations using two units to PING each other.

Various Screen Displays



PINGER PLUS+ displays results of a PING to a remote device. The MAC Address is displayed by pressing Info key.



PINGER PLUS+ Ping Received screen shows the IP and MAC address of the PING source.



PINGER PLUS+ displays the responding IP Address of the DHCP Server and the IP Address assigned to the PINGER PLUS+ .



PINGER PLUS+ Transmits a pattern of Link Signals that causes the hub, switch or NIC Link LED to blink or stay illuminated continuously.

Specifications

Physical

Dimensions: 7.0 in. x 3.2 in. x 1.4 in.
17.8 cm x 8.1 cm x 3.6 cm
Weight : 8.7 ounces
(w/batteries) 247 grams

Power

Four AA Alkaline Batteries (Included)
AC Adapter for Extended Operation

Environment

Operating Temperature: 0° to 50°C
Storage Temperature: -10° to 55°C

Display

Graphical - 122 x 32 pixels

Network types

10/100 Auto Negotiating
10baseT
100baseT
1000baseTX Identifies the connection only. No Test Performed.

Connector Type

One - RJ-45
(Combined port for LAN or NIC)

Product design and specifications subject to change without notice.

Ordering Information

PINGER PLUS+ Model 65 Network IP Tester

Includes: User Guide
AC Power Adapter
Four AA Alkaline Batteries

Psiber Data Systems Inc

7075-K Mission Gorge Road
San Diego, California 92120 USA

Phone: 619-287-9970

FAX: 619-287-9978

Internet: www.psiber.com

e-mail: info@psiber.com

Psiber Data GmbH

Am Soeldnermoos 17
85399 Hallbergmoos
Germany

Phone: +49 (0) 89 607 68610

FAX: +49 (0) 89 607 68611

Internet: www.psiber-data.com

e-mail: info@psiber-data.com

© 2003 Psiber Data Systems Inc.
All Rights Reserved. The Psiber Logo,
psiber, and PINGER PLUS+ are trademarks of
Psiber Data Systems Inc.

0101-0065-0001 Rev. A Printed in U.S.A.

