

REVISION

REV.A/0

- 1.CABLE; (A)28AWG(7/0.12TC),NON-UI,NON-FOIL,2C+S,OD=3.0±0.2mm,BLACK COLOR,PVC JACKET. (B)28AWG(7/0.12TC),UL2919,AL+D+B,{[(28AWG\*1C+D+AL)\*3COAX+28AWG\*5.5PAIR]},OD=9.0±0.2mm.BLACK WITH EMBOSS,PVC JACKET.
- 2. LENGTH: L.
- 3. CONNECTORS: HDB15M\*2PCS(BLACK INSULATOR), Ø3.5 STEREO PLUG\*2PCS(三段式)(SHELL NICKEL).

DRAWN

**DESIGNED** BY **APPROVAL** 

BY

- 4. MOLD: MOLDING TYPE.
- 5. SCREW:四方模螺絲\*4PCS.

DATE

2015.04.14

6. CONTACTS:

•	CONTACT																						
	HDB15P															64							
	HDB15P	1 RC	6 RG	2 BC	7 BG	3 cc	8 66	4 14 PAIR	5 P	12 ĂIR	10 P/	13 (IR	11 P	15 ÃIR	9	64 SHELL							
								ø3.	5 S	TEREC	PLU	JG(P1	)   .	1	2	9 64 SHELL							
								<u> </u>	5 5	TEREC	PII	IC/P2	<u>، ۱</u>	,		64							

7. Test machine test condition. A.100% OPEN, SHORT&INTERMITANCE TEST. B.CONDUCTOR RESISTANCE: 3ohms MAX:

C.INSULATION RESISTANCE: 5M Min/,10ms: 8. ALL MUST BE MEET ON ROHS COMPLIANT. ITEM NO. COMPANY MRP

DISCRIPTION

PĂIR			Printing PE BAG (COLOR: BLACK)	COLOR: BLACK (印刷不可掉色)  XXFT SVGA+3.5MM STEREO BLACK W/FERRITE CABLE 1PCS/PE BAG				
SVST-3MM	NO B				S/IL BAO			
					SCALE			
	SPEC		Stellar Labs Compute	er +	UNIT(mm)	$\oplus\Box$		
					PAGE	1/1		

40mm

RoHS

Printing CTN(BLUE)

20<sub>mm</sub>

COLOR: BLACK

RoHS