

<b>PO:</b>	<b>Cello Electronics (UK) Ltd.</b>	
	<b>Product Photo</b>	
<b>General Feature</b>	<b>Customer Model No.(Brand)</b>	C22230F Traveller
	<b>Panel(60Hz/120Hz/3D)</b>	LM215WF4(60Hz)
	<b>Destination Country</b>	UK
	<b>Safety and Regulation</b>	CE,ROHS
	<b>Panel System</b>	21.5 inch LED Panel(Approx. 55cm)
	<b>Purpose</b>	TV/Monitor Optional
	<b>Aspect Ratio</b>	16:9
	<b>Max. Resolution</b>	1920X1080
	<b>Contrast Ratio (Typical)</b>	600:1(TYP) by panel
	<b>Brightness(TYP cd/m2)</b>	200nits(TYP) by panel
	<b>Display Area(mm)</b>	479.0x270.0
	<b>Pixel Pitch (mm)</b>	0.08265 (H) x 0.24795(V)
	<b>Display Colors</b>	16.7M
	<b>Viewing Angle( H/V )</b>	0(CR≥10)/85/85/80/80(CR≥10)/85/85/80/80(CR≥10)
	<b>HD Supported Definitions</b>	1080p/1080i/720P/576P/480P
	<b>Response Time(Tr+Tf /typ.)</b>	5ms
	<b>Switch</b>	YES
<b>Cabinet Color</b>	Piano Black	
<b>Wall Mounting Support(Screw Size)</b>	VESA, 100 x 100mm(M4*8 )	
<b>Reception</b>	<b>TV Solution</b>	Mstar3463
	<b>TV System</b>	ATV: PAL BG/DK/I SECAM BG/DK/L/L' DTV: DVB-T & DVB-C & DVB-S2 & DVBT2, MPEG 2,MP@ML, MPEG 4 & H.265
	<b>TV Band</b>	ATV 49MHz - 863MHz DTV VHF (174MHz-- 230MHz) UHF (474MHz-- 862MHz)  DVB-S2 (950MHz-- 2150MHz)ATV 49MHz - 863MHz DTV VHF (174MHz-- 230MHz) UHF (474MHz-- 862MHz)  DVB-S2 (950MHz-- 2150MHz)ATV 49MHz - 863MHz DTV VHF (174MHz-- 230MHz) UHF (474MHz-- 862MHz)  DVB-S2 (950MHz-- 2150MHz)ATV 49MHz - 863MHz DTV VHF (174MHz-- 230MHz) UHF (474MHz-- 862MHz)  DVB-S2 (950MHz-- 2150MHz)ATV 49MHz - 863MHz DTV VHF (174MHz-- 230MHz) UHF (474MHz-- 862MHz)  DVB-S2 (950MHz-- 2150MHz)
	<b>In Menu 5V Aerial boost</b>	YES
	<b>Digital Comb Filter</b>	3D
	<b>Tuning System</b>	FST
	<b>Clock / Time Display</b>	N/A
	<b>CI PLUS</b>	YES
	<b>PCB internal Voltage support</b>	9-30V
	<b>Number of channel for storing</b>	100 Analog / 400 Digital
	<b>Sound</b>	<b>Bass</b>
<b>Treble</b>		YES
<b>Balance</b>		YES
<b>Sound Mode</b>		Standard / Music /Movie / Sports /User
<b>Stereo System</b>		NICAM/A2
<b>Audio Output</b>		2*3W

Connectors Jack	RF Antenna	2	
	HDMI	YES×2(ver1.4)	
	CVBS	YES×1(Mini Jack)	
	PC In	D-sub 15Pin × 1	
	Audio In	PC audio x 1(3.5 φ Mini Jack) CVBS Audio x1(Mini Jack ,Shared wih Ypbpr) PC audio x 1(3.5 φ Mini Jack) CVBS Audio x1(Mini Jack ,Shared wih Ypbpr) PC audio x 1(3.5 φ Mini Jack) CVBS Audio x1(Mini Jack ,Shared wih Ypbpr) PC audio x 1(3.5 φ Mini Jack) CVBS Audio x1(Mini Jack ,Shared wih Ypbpr)	
	Scart	YES× 1	
	YPbPr	YES× 1(Mini Jack)	
	Digital Audio Out	YES× 1	
	Earphone Out	YESx 1(3.5 φ Mini Jack)	
	USB	YESx 1( Multi Media and PVR Movie: *.mpg, *.dat, *.vob, *.avi, *.ts, *.mov, *.mkv, *.mp4 Music: *.mp3, *.wma, *.m4a, *.aac Photo: *.jpg, *.bmp, *.png)YESx 1( Multi Media and PVR Movie: *.mpg, *.dat, *.vob, *.avi, *.ts, *.mov, *.mkv, *.mp4 Music: *.mp3, *.wma, *.m4a, *.aac Photo: *.jpg, *.bmp, *.png)YESx 1( Multi Media and PVR Movie: *.mpg, *.dat, *.vob, *.avi, *.ts, *.mov, *.mkv, *.mp4 Music: *.mp3, *.wma, *.m4a, *.aac Photo: *.jpg, *.bmp, *.png)	
	CI	YES× 1	
	RCA	N/A	
	DVD	DVD Loader	FORYOU
		DVD Solution	MTK-MTK1389
DVD/DVD-R/DVD+R/DVD-RW/DVD+RW/CD/MP3/JPEG playbackDVD/DVD-R/DVD+R/DVD-RW/DVD+RW/CD/MP3/JPEG playbackDVD/DVD-R/DVD+R/DVD-RW/DVD+RW/CD/MP3/JPEG playback		YES	
DVD Reverse Play		YES	
Skip Forward/Reverse		YES	
DVD Multi-Speed Scan/Slow		YES	
Slot-Load Type Vertical Play DVD Mechanism		YES	
DIV X		\	
Other Features		APS (Channel installation programme)	ATV, DVBT, DVBC storage of channels in capture order. DVBS2 is a pre-set channel list.
	OSD Language	English / French / German / Italian/Spanish/Portuguese	
	OSD Language	Italian/Spanish/Portuguese	
	Teletext	1000pages	
	EPG (Electronic Program Guide)	7 days (not 7 days from satellite transmissions)	
	Automatic Tuning	YES	
	Sleep Timer	YES(240min)	
	Noise Reduction	YES	
	Color Temperature Adjustment	YES	
	Picture Mode	Standard /Dynamic/Mild /User	
Power	Home Power Supply	DC 12V/3.5A/AC 100V-240V~ 50Hz/60Hz	
	Operation Power Consumption	15W	
	Max power Consumption	<36W	
	Standby Power Consumption	0.4W	
	Energy Efficiency Class	A+	
Accessories	USER'S Manual	ENGLISH	
	Remote Control	YES× 1	
	Quick Start Guide	YES× 1	

	Wall 240V Plug (12V) Adapter with cable	YES x1
	Car Adapter Cable 12/24V	YES x1
	Warranty	YES
	Battery	1.5V(AAA)*2
Dimension	Unit Dimension With Stand (W x H x D mm)	520*362*160
	Unit Dimension Without Stand (W x H x D mm)	520*325*68
	Weight of unit(kg)	4.2
	Weight of gift box with content(kg)	/
	Weight of carton/paper(Kg)	/
	Weight of styrofoam(Kg)	/